

# MURS480ET3G

## SWITCHMODE Power Rectifiers

### Ultrafast “E” Series with High Reverse Energy Capability

These state-of-the-art devices are designed for use in switching power supplies, inverters and as free wheeling diodes.

#### Features

- 20 mJ Avalanche Energy Guaranteed
- Excellent Protection Against Voltage Transients in Switching Inductive Load Circuits
- Ultrafast 75 Nanosecond Recovery Time
- 175°C Operating Junction Temperature
- Low Forward Voltage
- Low Leakage Current
- High Temperature Glass Passivated Junction
- Reverse Voltage to 800 V
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

#### Mechanical Characteristics:

- Case: Epoxy, Molded
- Weight: 217 mg (Approximately)
- Finish: All External Surfaces Corrosion Resistant and Terminal Leads are Readily Solderable
- Lead Temperature for Soldering Purposes: 260°C Max. for 10 Seconds
- Shipped in 16 mm Tape & Reel, 2500 Units per Reel
- Polarity: Polarity Band on Plastic Body Indicates Cathode Lead

#### MAXIMUM RATINGS

| Rating                                                                                                         | Symbol                          | Value                            | Unit |
|----------------------------------------------------------------------------------------------------------------|---------------------------------|----------------------------------|------|
| Peak Repetitive Reverse Voltage<br>Working Peak Reverse Voltage<br>DC Blocking Voltage<br>MURS480E             | $V_{RRM}$<br>$V_{RWM}$<br>$V_R$ | 800                              | V    |
| Average Rectified Forward Current                                                                              | $I_{F(AV)}$                     | 4.0 @<br>$T_L=110^\circ\text{C}$ | A    |
| Non-Repetitive Peak Surge Current<br>(Surge Applied at Rated Load Conditions<br>Halfwave, Single Phase, 60 Hz) | $I_{FSM}$                       | 70                               | A    |
| Operating Junction and Storage Temperature Range                                                               | $T_J, T_{stg}$                  | -65 to<br>+175                   | °C   |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



ON Semiconductor®


[www.onsemi.com](http://www.onsemi.com)

### ULTRAFAST RECTIFIER 4.0 AMPERES, 800 VOLTS



SMC 2-LEAD  
CASE 403AC

#### MARKING DIAGRAM



U4 = Specific Device Code  
A = Assembly Location\*  
Y = Year  
WW = Work Week

\*The Assembly Location code (A) is front side optional. In cases where the Assembly Location is stamped in the package, the front side assembly code may be blank.

#### ORDERING INFORMATION

| Device      | Package          | Shipping†        |
|-------------|------------------|------------------|
| MURS480ET3G | SMC<br>(Pb-Free) | 2500/Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MURS480ET3G

## THERMAL CHARACTERISTICS

| Rating                                          | Symbol          | Value | Unit                 |
|-------------------------------------------------|-----------------|-------|----------------------|
| Maximum Thermal Resistance, Junction-to-Lead    | $R_{\theta JL}$ | 11    | $^{\circ}\text{C/W}$ |
| Maximum Thermal Resistance, Junction-to-Ambient | $R_{\theta JA}$ | 165   | $^{\circ}\text{C/W}$ |






## ELECTRICAL CHARACTERISTICS

| Characteristic                                                                                                                                                                                              | Symbol     | Max                  | Unit          |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------------------|---------------|
| Maximum Instantaneous Forward Voltage (Note 1)<br>( $I_F = 3.0$ Amps, $T_J = 150^{\circ}\text{C}$ )<br>( $I_F = 3.0$ Amps, $T_J = 25^{\circ}\text{C}$ )<br>( $I_F = 4.0$ Amps, $T_J = 25^{\circ}\text{C}$ ) | $V_F$      | 1.53<br>1.75<br>1.85 | V             |
| Maximum Instantaneous Reverse Current (Note 1)<br>(Rated dc Voltage, $T_J = 150^{\circ}\text{C}$ )<br>(Rated dc Voltage, $T_J = 25^{\circ}\text{C}$ )                                                       | $i_R$      | 900<br>25            | $\mu\text{A}$ |
| Maximum Reverse Recovery Time<br>( $I_F = 1.0$ A, $di/dt = 50$ A/ $\mu\text{s}$ )<br>( $I_F = 0.5$ A, $i_R = 1.0$ A, $I_{REC} = 0.25$ A)                                                                    | $t_{rr}$   | 100<br>75            | ns            |
| Maximum Forward Recovery Time<br>( $I_F = 1.0$ Amp, $di/dt = 100$ Amp/ $\mu\text{s}$ , Recovery to 1.0 V)                                                                                                   | $t_{fr}$   | 75                   | ns            |
| Controlled Avalanche Energy                                                                                                                                                                                 | $W_{AVAL}$ | 20                   | mJ            |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

1. Pulse Test: Pulse Width = 300  $\mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .

TYPICAL ELECTRICAL CHARACTERISTICS



# MECHANICAL CASE OUTLINE





## PACKAGE DIMENSIONS



SCALE 1:1

### SMC 2-LEAD CASE 403AC ISSUE B

DATE 27 JUL 2017



#### GENERIC MARKING DIAGRAM\*



XXXX = Specific Device Code  
A = Assembly Location  
Y = Year  
WW = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)


\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANME Y14.5M, 1994.
2. CONTROLLING DIMENSION: INCHES.
3. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.254mm PER SIDE.
4. DIMENSIONS D AND E TO BE DETERMINED AT DATUM H.
5. DIMENSION b SHALL BE MEASURED WITHIN THE AREA DETERMINED BY DIMENSION L.

| DIM            | MILLIMETERS |      | INCHES |       |
|----------------|-------------|------|--------|-------|
|                | MIN         | MAX  | MIN    | MAX   |
| A              | 1.95        | 2.61 | 0.077  | 0.103 |
| A1             | 0.05        | 0.20 | 0.002  | 0.008 |
| A2             | 1.90        | 2.41 | 0.075  | 0.095 |
| b              | 2.90        | 3.20 | 0.114  | 0.126 |
| c              | 0.15        | 0.41 | 0.006  | 0.016 |
| D              | 5.55        | 6.25 | 0.219  | 0.246 |
| E              | 6.60        | 7.15 | 0.260  | 0.281 |
| H <sub>E</sub> | 7.75        | 8.15 | 0.305  | 0.321 |
| L              | 0.75        | 1.60 | 0.030  | 0.063 |

#### RECOMMENDED SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

|                         |                    |                                                                                                                                                                                     |
|-------------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON97675F</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SMC 2-LEAD</b>  | <b>PAGE 1 OF 1</b>                                                                                                                                                                  |

**onsemi** and **onsemi** are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)