IXYS

1200V XPT™ Gen 4 IGBT

IXYX110N120C4

V_{CES} = 1200V
I_{C110} = 110A
$V_{CE(sat)}$ ≤ 2.40V
$t_{fi(typ)}$ = 37ns

High Speed IGBT for
20-50kHz Switching



PLUS247
(IXYX)



G = Gate C = Collector
E = Emitter Tab = Collector

Symbol	Test Conditions	Maximum Ratings	
V_{CES}	T_J = 25°C to 175°C	1200	V
V_{CGR}	T_J = 25°C to 175°C, R_{GE} = 1MΩ	1200	V
V_{GES}	Continuous	±20	V
V_{GEM}	Transient	±30	V
I_{C25}	T_C= 25°C (Chip Capability)	310	A
I_{LRMS}	Terminal Current Limit	160	A
I_{C110}	T_C= 110°C	110	A
I_{CM}	T_C = 25°C, 1ms	740	A
SSOA	V_{GE} = 15V, T_{VJ} = 150°C, R_G = 2Ω	I_{CM} = 220	A
(RBSOA)	Clamped Inductive Load	0.8 • V_{CES}	V
P_C	T_C = 25°C	1360	W
T_J		-55 ... +175	°C
T_{JM}		175	°C
T_{stg}		-55 ... +175	°C
T_L	Maximum Lead Temperature for Soldering	300	°C
T_{SOLD}	1.6 mm (0.062 in.) from Case for 10s	260	°C
F_C	Mounting Force	20..120 /4.5..27	N/lb
Weight		6	g

Symbol	Test Conditions (T_J = 25°C, Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.	
BV_{CES}	I_C = 250μA, V_{GE} = 0V	1200			V
$V_{GE(th)}$	I_C = 3mA, V_{CE} = V_{GE}	4.5		6.5	V
I_{CES}	V_{CE} = V_{CES}, V_{GE} = 0V			25	μA
	T_J = 150°C			1.5	mA
I_{GES}	V_{CE} = 0V, V_{GE} = ±20V			±100	nA
$V_{CE(sat)}$	I_C = I_{C110}, V_{GE} = 15V, Note 1		1.90	2.40	V
	T_J = 150°C		2.27		V

Features

- Optimized for Low Switching Losses
- Positive Thermal Coefficient of Vce(sat)
- International Standard Package

Advantages

- High Power Density
- Low Gate Drive Requirement

Applications

- Power Inverters
- UPS
- Motor Drives
- SMPS
- PFC Circuits
- Battery Chargers
- Welding Machines
- Lamp Ballasts

©2021 Littelfuse, Inc.

Symbol	Test Conditions (T_J = 25°C Unless Otherwise Specified)	Characteristic Values Min.	Typ.	Max.
g_{fs}	I_C = 60A, V_{CE} = 10V, Note 1	40	68	S
C_{ies}	V_{CE} = 25V, V_{GE} = 0V, f = 1MHz		5420	pF
C_{oes}			335	pF
C_{res}			220	pF
$Q_{g(on)}$	$I_C = I_{C110}$, V_{GE} = 15V, $V_{CE} = 0.5 \bullet V_{CES}$		330	nC
Q_{ge}			55	nC
Q_{gc}			138	nC
$t_{d(on)}$	**Inductive load, T_J = 25°C**		40	ns
t_{ri}	I_C = 50A, V_{GE} = 15V		48	ns
E_{on}	$V_{CE} = 0.5 \bullet V_{CES}$, $R_G = 2\Omega$		3.6	mJ
$t_{d(off)}$	Note 2		320	ns
t_{fi}			37	ns
E_{off}			1.9	mJ
$t_{d(on)}$	**Inductive load, T_J = 150°C**		36	ns
t_{ri}	I_C = 50A, V_{GE} = 15V		37	ns
E_{on}	$V_{CE} = 0.5 \bullet V_{CES}$, $R_G = 2\Omega$		5.3	mJ
$t_{d(off)}$	Note 2		326	ns
t_{fi}			90	ns
E_{off}			3.2	mJ
R_{thJC}				0.11 °C/W
R_{thCS}			0.15	°C/W

Notes:

1. Pulse test, t ≤ 300µs, duty cycle, d ≤ 2%.
2. Switching times & energy losses may increase for higher V_{CE}(clamp), T_J or R_G.

Littelfuse reserves the right to change limits, test conditions, and dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,860,072 4,881,106 4,931,844 5,017,508 5,034,796 5,049,961 5,063,307 5,187,117 5,237,481 5,381,025 5,486,715 6,162,665 6,259,123 B1 6,306,728 B1 6,404,065 B1 6,534,343 6,583,505 6,683,344 6,710,405 B2 6,710,463 6,727,585 6,759,692 6,771,478 B2 7,005,734 B2 7,063,975 B2 7,071,537 7,157,338B2

Fig. 1. Output Characteristics @ T_J = 25ºC



Fig. 2. Extended Output Characteristics @ T_J = 25ºC



Fig. 3. Output Characteristics @ T_J = 150ºC



Fig. 4. Dependence of $V_{CE(sat)}$ on Junction Temperature



Fig. 5. Collector-to-Emitter Voltage vs. Gate-to-Emitter Voltage



Fig. 6. Input Admittance



©2021 Littelfuse, Inc.

Fig. 7. Transconductance



Fig. 8. Gate Charge



Fig. 9. Capacitance



Fig. 10. Reverse-Bias Safe Operating Area



Fig. 11. Maximum Transient Thermal Impedance



Littelfuse reserves the right to change limits, test conditions, and dimensions.

Fig. 12. Inductive Switching Energy Loss vs. Collector Current



Fig. 13. Inductive Switching Energy Loss vs. Collector-Emitter Voltage



Fig. 14. Inductive Switching Energy Loss vs. Gate Resistance



Fig. 15. Inductive Switching Energy Loss vs. Junction Temperature



Fig. 16. Inductive Turn-off Switching Times vs. Gate Resistance



Fig. 17. Inductive Turn-off Switching Times vs. Collector Current



©2021 Littelfuse, Inc.

Fig. 18. Inductive Turn-off Switching Times vs. Junction Temperature



Fig. 19. Inductive Turn-on Switching Times vs. Gate Resistance



Fig. 20. Inductive Turn-on Switching Times vs. Collector Current



Fig. 21. Inductive Turn-on Switching Times vs. Junction Temperature



Littelfuse reserves the right to change limits, test conditions, and dimensions.

PLUS247™ Outline



1 - Gate
2,4 - Collector
3 - Emitter

SYM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.190	.205	4.83	5.21
A1	.090	.100	2.29	2.54
A2	.075	.085	1.91	2.16
b	.045	.055	1.14	1.40
b2	.075	.087	1.91	2.20
b4	.115	.126	2.92	3.20
C	.024	.031	0.61	0.80
D	.819	.840	20.80	21.34
D1	.650	.690	16.51	17.53
D2	.035	.050	0.89	1.27
E	.620	.635	15.75	16.13
E1	.520	.560	13.08	14.22
e	.215 BSC		5.45 BSC	
L	.780	.810	19.81	20.57
L1	.150	.170	3.81	4.32
Q	.220	.244	5.59	6.20
R	.170	.190	4.32	4.83

IXYS
A Littelfuse Technology

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

©2021 Littelfuse, Inc.