

## BZT52B2V4 - BZT52B43 ZENER DIODES



### Features

- Planar Die Construction
- 350mW Power Dissipation on Ceramic PCB
- General Purpose, Medium Current
- Ideally Suited for Automated Assembly Processes
- Available in Lead Free Version
- This is a Halogen Free Device
- All SMC parts are traceable to the wafer lot
- Additional testing can be offered upon request

### Circuit Diagram



### Mechanical Data

- Case: SOD-123, Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band
- Weight: 0.01 grams(approx)

### Maximum Ratings @ $T_A=25^{\circ}\text{C}$ unless otherwise specified

| Characteristic                               | Symbol          | Value       | Units                |
|--|-----------------|-------------|----------------------|
| Forward Voltage (Note 2) @ $I_F=10\text{mA}$ | $V_F$           | 0.9         | V                    |
| Power Dissipation(Note 1)                    | $P_D$           | 350         | mW                   |
| Thermal resistance junction to Ambient       | $R_{\theta JA}$ | 357         | $^{\circ}\text{C/W}$ |
| Junction Temperature                         | $T_J$           | 150         | $^{\circ}\text{C}$   |
| Storage Temperature Range                    | $T_{STG}$       | -55 to +150 | $^{\circ}\text{C}$   |


**Electrical Characteristics @T<sub>A</sub>=25°C unless otherwise specified**

| Type Number | Type Code | Zener Voltage Range (Note 2)    |        |        |                 | Maximum Zener Impedance (Note 3) |                                  |                 | Maximum Reverse Current |                | Typical Temperature Coefficient @I <sub>ZTC</sub> |      | Test Current I <sub>ZTC</sub> |
|-------------|-----------|---------------------------------|--------|--------|-----------------|----------------------------------|----------------------------------|-----------------|-------------------------|----------------|---|------|-------------------------------|
|             |           | V <sub>Z</sub> @I <sub>ZT</sub> |        |        | I <sub>ZT</sub> | Z <sub>ZT</sub> @I <sub>ZT</sub> | Z <sub>ZK</sub> @I <sub>ZK</sub> | I <sub>ZK</sub> | I <sub>R</sub>          | V <sub>R</sub> | mV/°C   |      |                               |
|             |           | Nom(V)                          | Min(V) | Max(V) | mA              | Ω                                |                                  | mA              | μA                      | V              | Min   | Max  |                               |
| BZT52B2V4   | 2WX       | 2.4                             | 2.35   | 2.45   | 5               | 100                              | 600                              | 1.0             | 50                      | 1.0            | -3.5  | 0    | 5                             |
| BZT52B2V7   | 2W1       | 2.7                             | 2.65   | 2.75   | 5               | 100                              | 600                              | 1.0             | 20                      | 1.0            | -3.5  | 0    | 5                             |
| BZT52B3V0   | 2W2       | 3.0                             | 2.94   | 3.06   | 5               | 95                               | 600                              | 1.0             | 10                      | 1.0            | -3.5  | 0    | 5                             |
| BZT52B3V3   | 2W3       | 3.3                             | 3.23   | 3.37   | 5               | 95                               | 600                              | 1.0             | 5                       | 1.0            | -3.5  | 0    | 5                             |
| BZT52B3V6   | 2W4       | 3.6                             | 3.53   | 3.67   | 5               | 90                               | 600                              | 1.0             | 5                       | 1.0            | -3.5  | 0    | 5                             |
| BZT52B3V9   | 2W5       | 3.9                             | 3.82   | 3.98   | 5               | 90                               | 600                              | 1.0             | 3                       | 1.0            | -3.5  | 0    | 5                             |
| BZT52B4V3   | 2W6       | 4.3                             | 4.21   | 4.39   | 5               | 90                               | 600                              | 1.0             | 3                       | 1.0            | -3.5  | 0    | 5                             |
| BZT52B4V7   | 2W7       | 4.7                             | 4.61   | 4.79   | 5               | 80                               | 500                              | 1.0             | 3                       | 2.0            | -3.5  | 0.2  | 5                             |
| BZT52B5V1   | 2W8       | 5.1                             | 5.00   | 5.20   | 5               | 60                               | 480                              | 1.0             | 2                       | 2.0            | -2.7  | 1.2  | 5                             |
| BZT52B5V6   | 2W9       | 5.6                             | 5.49   | 5.71   | 5               | 40                               | 400                              | 1.0             | 1                       | 2.0            | -2.0  | 2.5  | 5                             |
| BZT52B6V2   | 2WA       | 6.2                             | 6.08   | 6.32   | 5               | 10                               | 150                              | 1.0             | 3                       | 4.0            | 0.4   | 3.7  | 5                             |
| BZT52B6V8   | 2WB       | 6.8                             | 6.66   | 6.94   | 5               | 15                               | 80                               | 1.0             | 2                       | 4.0            | 1.2   | 4.5  | 5                             |
| BZT52B7V5   | 2WC       | 7.5                             | 7.35   | 7.65   | 5               | 15                               | 80                               | 1.0             | 1                       | 5.0            | 2.5   | 5.3  | 5                             |
| BZT52B8V2   | 2WD       | 8.2                             | 8.04   | 8.36   | 5               | 15                               | 80                               | 1.0             | 0.7                     | 5.0            | 3.2   | 6.2  | 5                             |
| BZT52B9V1   | 2WE       | 9.1                             | 8.92   | 9.28   | 5               | 15                               | 100                              | 1.0             | 0.5                     | 6.0            | 3.8   | 7.0  | 5                             |
| BZT52B10    | 2WF       | 10                              | 9.80   | 10.20  | 5               | 20                               | 150                              | 1.0             | 0.2                     | 7.0            | 4.5   | 8.0  | 5                             |
| BZT52B11    | 2WG       | 11                              | 10.78  | 11.22  | 5               | 20                               | 150                              | 1.0             | 0.1                     | 8.0            | 5.4   | 9.0  | 5                             |
| BZT52B12    | 2WH       | 12                              | 11.76  | 12.24  | 5               | 25                               | 150                              | 1.0             | 0.1                     | 8.0            | 6.0   | 10.0 | 5                             |
| BZT52B13    | 2WI       | 13                              | 12.74  | 13.26  | 5               | 30                               | 170                              | 1.0             | 0.1                     | 8.0            | 7.0   | 11.0 | 5                             |
| BZT52B15    | 2WJ       | 15                              | 14.70  | 15.30  | 5               | 30                               | 200                              | 1.0             | 0.1                     | 10.5           | 9.2   | 13.0 | 5                             |
| BZT52B16    | 2WK       | 16                              | 15.68  | 16.32  | 5               | 40                               | 200                              | 1.0             | 0.1                     | 11.2           | 10.4  | 14.0 | 5                             |
| BZT52B18    | 2WL       | 18                              | 17.64  | 18.36  | 5               | 45                               | 225                              | 1.0             | 0.1                     | 12.6           | 12.4  | 16.0 | 5                             |
| BZT52B20    | 2WM       | 20                              | 19.60  | 20.40  | 5               | 55                               | 225                              | 1.0             | 0.1                     | 14.0           | 14.4  | 18.0 | 5                             |
| BZT52B22    | 2WN       | 22                              | 21.56  | 22.44  | 5               | 55                               | 250                              | 1.0             | 0.1                     | 15.4           | 16.4  | 20.0 | 5                             |
| BZT52B24    | 2WO       | 24                              | 23.52  | 24.48  | 5               | 70                               | 250                              | 1.0             | 0.1                     | 16.8           | 18.4  | 22.0 | 5                             |
| BZT52B27    | 2WP       | 27                              | 26.46  | 27.54  | 2               | 80                               | 300                              | 0.5             | 0.1                     | 18.9           | 21.4  | 25.3 | 2                             |
| BZT52B30    | 2WQ       | 30                              | 29.40  | 30.60  | 2               | 80                               | 300                              | 0.5             | 0.1                     | 21.0           | 24.4  | 29.4 | 2                             |
| BZT52B33    | 2WR       | 33                              | 32.34  | 33.66  | 2               | 80                               | 325                              | 0.5             | 0.1                     | 23.1           | 27.4  | 33.4 | 2                             |
| BZT52B36    | 2WS       | 36                              | 35.28  | 36.72  | 2               | 90                               | 350                              | 0.5             | 0.1                     | 25.2           | 30.4  | 37.4 | 2                             |
| BZT52B39    | 2WT       | 39                              | 38.22  | 39.78  | 2               | 130                              | 350                              | 0.5             | 0.1                     | 27.3           | 33.4  | 41.2 | 2                             |
| BZT52B43    | 2WU       | 43                              | 41.16  | 42.84  | 2               | 130                              | 350                              | 0.5             | 0.1                     | 29.4           | 36.4  | 45.2 | 2                             |


Notes: 1. Device mounted on ceramic PCB: 7.6mm x 9.4mm x 0.87mm with pad areas 25mm<sup>2</sup>  
 2. Short duration test pulse used to minimize self-heating effect  
 3. f = 1kHz

**Ratings and Characteristics Curves**


**Zener Characteristics ( $V_z$  5.1V to 20 V)**




**Temperature Coefficients**




**Typical Leakage Current**




**Typical Capacitance**




**Effect of Zener Voltage on Zener Impedance**



**Power Derating Curve**




**Mechanical Dimensions SOD-123**


| SYMBOL   | Millimeters |       | Inches     |       |
|----------|-------------|-------|------------|-------|
|          | MIN.        | MAX.  | MIN.       | MAX.  |
| A        | 1.050       | 1.250 | 0.041      | 0.049 |
| A1       | 0.000       | 0.100 | 0.000      | 0.004 |
| A2       | 1.050       | 1.150 | 0.041      | 0.045 |
| b        | 0.450       | 0.650 | 0.018      | 0.026 |
| c        | 0.080       | 0.150 | 0.003      | 0.006 |
| D        | 1.500       | 1.700 | 0.059      | 0.067 |
| E        | 2.600       | 2.800 | 0.102      | 0.110 |
| E1       | 3.550       | 3.850 | 0.140      | 0.152 |
| L        | 0.500 REF.  |       | 0.020 REF. |       |
| L1       | 0.250       | 0.450 | 0.010      | 0.018 |
| $\theta$ | 0°          | 8°    | 0°         | 8°    |


**Ordering Information**

| Device                      | Package | Shipping       |
|-----------------------------|---------|----------------|
| BZT52B2V4 -<br>BZT52B43     | SOD-123 | 3000pcs / reel |
| BZT52B2V4TR -<br>BZT52B43TR | SOD-123 | 3000pcs / reel |

For information on tape and reel specifications, including part orientation and tape sizes, please refer to our tape and reel packaging specification.

**Marking Diagram**


2WX = Type code

**Carrier Tape Specification SOD-123**


| SYMBOL | Millimeters |      |
|--------|-------------|------|
|        | Min.        | Max. |
| A      | 1.80        | 1.90 |
| B      | 3.89        | 3.99 |
| C      | 1.52        | 1.62 |
| d      | 1.45        | 1.65 |
| E      | 1.65        | 1.85 |
| F      | 3.40        | 3.60 |
| P      | 3.90        | 4.10 |
| P0     | 3.90        | 4.10 |
| P1     | 1.90        | 2.10 |
| W      | 7.90        | 8.30 |

**DISCLAIMER:**

1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the SMC Diode Solutions sales department for the latest version of the datasheet(s).

2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.

3- In no event shall SMC Diode Solutions be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). SMC Diode Solution assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.

4- In no event shall SMC Diode Solutions be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.

5- No license is granted by the datasheet(s) under any patents or other rights of any third party or SMC Diode Solutions.

6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of SMC Diode Solutions.

7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations..