


SPECIFICATION CONTROL DRAWING




Product Revision		Ident Code	Product Dimensions			Cable Dimensions			
Product Name			L±1.75 (L±0.075)	øB min	øC min	øD max	øE max	øF min	øG min
SO175-1-55-22-90	A	SO1751R	16.50 (0.650)	1.90 (0.075)	2.67 (0.105)	1.90 (0.075)	2.67 (0.105)	0.90 (0.035)	0.50 (0.020)
SO175-2-55-22-90	A	SO1752R	16.50 (0.650)	2.67 (0.105)	3.68 (0.145)	1.90 (0.075)	3.68 (0.145)	1.40 (0.055)	0.75 (0.030)
SO175-3-55-22-90	A	SO1753R	16.50 (0.650)	4.32 (0.170)	5.08 (0.200)	4.32 (0.170)	5.08 (0.200)	2.15 (0.085)	1.25 (0.050)
SO175-4-55-22-90	A	SO1754R	19.10 (0.750)	5.97 (0.235)	6.48 (0.255)	5.97 (0.235)	6.48 (0.255)	3.30 (0.130)	1.80 (0.070)
SO175-5-55-22-90	A	SO1755R	19.10 (0.750)	6.98 (0.275)	7.62 (0.300)	6.98 (0.275)	7.62 (0.300)	4.30 (0.170)	2.50 (0.100)

MATERIALS

- INSULATION SLEEVE: Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.
- SOLDER PREFORM WITH FLUX AND THERMAL INDICATOR:
 - SOLDER: TYPE Sn96 per ANSI/J-STD-006.
 - FLUX: TYPE ROM1 per ANSI/J-STD-004.
 - THERMAL INDICATOR: Fusible ring, melt point: 232°C, completely melted at 240°C.
 - MELTABLE RINGS: Environment resistant thermoplastic. Color: blue.
- PRE-INSTALLED LEAD: Raychem 55A0813-22-90 in accordance with MIL-W-22759/41-22-90 AWG22 stranded nickel-plated copper. Color: white with black stripe.

APPLICATION

- These parts are designed to provide an environment resistant shield termination on cables, rated for 150°C minimum, meeting the dimensional criteria listed, having nickel-plated shields and insulations compatible with the insert material. For compatible insulations, consult Tyco Electronics/Raychem.
- When installed per Tyco Electronics/Raychem process standard RCPS-100-70, assemblies will meet performance requirement Raychem Specification RT-1404, and 514.1920/99 Aerospatiale Matra Specification.
- Parts shall be marked with identification code per table.
- Temperature range: -55°C to +175°C.
For best results, prepare the cable as shown:



SolderSleeve is a trademark of Tyco Electronics Corporation.

tyco Electronics		Tyco Electronics Corporation 300 Constitution Drive, Menlo Park, CA. 94025, U.S.A.		Raychem		TITLE: SOLDERSLEEVE DEVICE SHIELD TERMINATION WITH LEADS, IMMERSION RESISTANT, 175°C, LEAD-FREE				
Unless otherwise specified dimensions are in millimeters. [Inches dimensions are shown in brackets]					DOCUMENT NO.: SO175-X-55-22-90					
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A		ANGLES: N/A		Tyco Electronics reserves the right to amend this drawing at any time. Users should evaluate the suitability of the product for their application.			PROD. REV.: SEE TABLE		DOC. ISSUE: 2	DATE: 27OCT2023
DRAWN BY: M. FORONDA		CAGE CODE: 06090					REPLACES: D020141		DCR NUMBER: D030221	

© 2022 TE Connectivity Ltd. Family of Companies. All Rights Reserved.

*TE Connectivity, TE connectivity (logo), Raychem, Thermofit, SolderSleeve are trademarks