

Revision Number: 005.0 Issue date: 04/24/2019

# 1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

**Product name: LOCTITE 370 SN60 5C 0.61MM S** 

known as SN60 Wrap3.025-1 500 GR

Spool

Product type/use: Solder Wire Item number: MM00992 Restriction of Use: None identified Region: **United States** 

Company address: Contact information:

Henkel Corporation Telephone: +1 (860) 571-5100

One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

386824

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

DANGER: HARMFUL IF SWALLOWED OR IF INHALED.

MAY CAUSE DROWSINESS OR DIZZINESS.

MAY DAMAGE FERTILITY OR THE UNBORN CHILD.

CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED

EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY ORAL	4
ACUTE TOXICITY INHALATION	4
REPRODUCTIVE TOXICITY	1A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1

#### PICTOGRAM(S)



#### **Precautionary Statements**

Response:

Obtain special instructions before use. Do not handle until all safety precautions have been Prevention:

read and understood. Do not breathe dust or fumes. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-

ventilated area. Wear protective gloves, clothing, eye and face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove victim to fresh

air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or

physician if you feel unwell. IF exposed or concerned: Get medical attention.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Storage: Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 386824 Product name: LOCTITE 370 SN60 5C 0.61MM S known as SN60 Wrap3.025-1 500 GR Spool Page 1 of 6

#### See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

	Hazardous Component(s)	CAS Number	Percentage*
	Tin	7440-31-5	30 - 60
	Lead	7439-92-1	30 - 60

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. If symptoms develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. If symptoms develop

and persist, get medical attention.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. Do not use water on fires where molten metal is present.

Unusual fire or explosion hazards: None

IDH number: 386824

**Hazardous combustion products:** Oxides of Carbon. Oxides of Metals in Section 3. Formaldehyde. High

temperatures may produce heavy metal dust, fumes or vapours. The flux

medium will give rise to irritating fumes.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Wear protective clothing, gloves and safety

glasses. Scrape up spilled material and place in a closed container for disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to

clean up.

# 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Wear suitable protective clothing, gloves

and eve/face protection. Avoid contact with eves, skin and clothing. Avoid skin contact with molten resins. When using, do not eat, drink or smoke. Wash

thoroughly after handling.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use. Store in original container

until ready to use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Tin	2 mg/m3 TWA	2 mg/m3 PEL (as Sn)	None	None
Lead	0.05 mg/m3 TWA (as Pb)	0.05 mg/m3 TWA 0.03 mg/m3 OSHA_ACT	None	None

**Engineering controls:** Use adequate ventilation to remove molten vapors or fumes. Provide

adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid Color: Gray Odor: Metallic Odor threshold: Not available.

pH: Not available. Vapor pressure: Not available. Boiling point/range: Not available. Melting point/ range: Not available.

Specific gravity: 8.5

IDH number: 386824

Vapor density: Not available. Flash point: Does not flash. Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable **Evaporation** rate: Not available. Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available. 0.00 %; 0 g/l **VOC** content: Viscosity: Not available. **Decomposition temperature:** Not available.

Product name: LOCTITE 370 SN60 5C 0.61MM S known as SN60 Wrap3.025-1 500 GR Spool

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 386824

Oxides of carbon. Oxides of Metals in Section 3. Formaldehyde. Thermal decomposition can

lead to release of irritating gases and vapors.

Incompatible materials: Strong oxidizing agents. Strong acids and strong bases.

Reactivity: Not available.

Solder alloy will react with concentrated nitric acid to produce toxic fumes of nitrogen oxides. Conditions to avoid:

# **TOXICOLOGICAL INFORMATION**

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation: Harmful if inhaled. Fumes and/or dust produced by this product may be hazardous in case of

ingestion or inhalation. Rosin thermal decomposition product (as formaldehyde) is classified by NIOSH as a potential occupational carcinogen. Excessive exposure to tin fumes or dust may cause Stannosis, a chronic respiratory disease resulting in reduced lung capacity and benign tumors. Lead is a cumulative poison and continuous exposure to small amounts over time can raise the body's content to toxic levels. Excessive inhalation of fumes from many metals can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever (very similar to and easily confused with flu symptoms) which come on a few hours after large

exposures. Vapor overexposure may cause drowsiness. Dizziness.

Skin contact: May cause skin irritation. Eye contact: May cause eye irritation.

Ingestion: Harmful if swallowed. Lead is a cumulative poison and continuous exposure to small amounts

over time can raise the body's content to toxic levels. Symptoms of lead poisoning include

abdominal pain, nausea, vomiting, and headache.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Tin	None	Gastrointestinal, Irritant, Kidney, Liver, Lung Nervous System	
Lead	None	Nervous System  Behavioral, Blood, Developmental, Eyes Gastrointestinal, Kidney, Liver, Muscle, Nervous System, Reproductive, Skin, Son evidence of carcinogenicity, Thyroid	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Tin	No	No	No
Lead	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

Product name: LOCTITE 370 SN60 5C 0.61MM S known as SN60 Wrap3.025-1 500 GR Spool

Page 4 of 6

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal. Do not

dispose of in an uncontrolled manner.

Hazardous waste number: D008: Lead

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

#### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

# 15. REGULATORY INFORMATION

### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis. CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Lead (CAS# 7439-92-1).

CERCLA Reportable quantity: Lead (CAS# 7439-92-1) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

IDH number: 386824 Product name: LOCTITE 370 SN60 5C 0.61MM S known as SN60 Wrap3.025-1 500 GR Spool Page 5 of 6

# 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 04/24/2019

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.