

DATE:

October

2022

## Features

- Under Stencil Rolls for JUKI Printers
- Prevents smearing, bridging, solder balls, and other problems associated with the stencil printing of solder paste
- Manufactured from a blend of polyester and cellulose fibers
- More paper per roll resulting in less down time, less changeover time, and less inventory required
- Exceptionally low lint levels
- Solvent resistant material results in increased absorption per square inch

## **JUKI Paper Specifications**

Test	Orientation	Units	Value	Method	
Composition			54% Wood Pulp 46% Polyester White		
Basis Weight		oz/yd² g/m²	1.5 50.8	ASTM D3776	
Thickness		mils mm	12 .30	ASTM D1777	
Grab Tensile Strength	Machine Direction	lb N	28 125	ASTM D5034	
	Cross Direction	lb N	16 71	A3 I WI D3034	

## JUKI Stencil Roll Part Numbers

Part Number	Core Type	Core Length	Paper Width	Core ID	Paper Length	Core Notch Width	Core Notch Depth	# of Notches on Core End 1	# of Notches on Core End 2
EB41J1616	Plastic	16"	15.5"	.75"	39'	0.125"	0.15"	2	2
EB41J1918	Plastic	18.5"	17.75"	.75"	39'	0.125"	0.15"	2	2
EB41J2120	Plastic	20.87"	20.12"	.75"	39'	0.125"	0.15"	2	2

## Notch Depth: ± 0.03" Specifications and procedures subject to change without notice. Sofk STERVE ROLES EasyBraid 11520 K-TEL DRIVE, MINNETONKA, MN 55343 (909) 627-2453 WEBSITE: EASYBRAIDCO.COM DRAWING NUMBER JUKI

© 2022 DESCO INDUSTRIES INC Employee Owned

**Dimensional Tolerances:** 

Core Length: ± 1/16" Paper Width: ± 1/8" Core ID: + 1/8" Paper Length: ± 5% Notch Width: ± 0.02"

