



## CMA/CMD SERIES | 480 VAC

PANEL MOUNT SOLID STATE RELAYS



### Features

- Ratings from 25A to 125A @ 48-530 VAC
- SCR output for heavy industrial loads
- DC control
- LED input status indicator
- Zero crossing (resistive loads) output
- IP20 touch-safe housing
- Standard box-clamp connections

### PRODUCT SELECTION

Control Voltage	25 A	50 A	125 A
4-32 VDC	CMD4825	CMD4850	CMD48125

### SPECIFICATIONS

#### Output <sup>(1)</sup>

Description	25 A	50 A	125 A
<b>Operating Voltage (47-63Hz) [Vrms]</b>	48-530	48-530	48-530
<b>Transient Overvoltage [Vpk]</b>	1200	1200	1200
<b>Maximum Off-State Leakage Current @ Rated Voltage [mA]</b>	10	10	10
<b>Minimum Off-State dv/dt @ Maximum Rated Voltage [V/μsec] <sup>(2)</sup></b>	500	500	500
<b>Maximum Load Current [Arms] <sup>(3)</sup></b>	25	50	125
<b>Minimum Load Current [Arms]</b>	0.15	0.15	0.25
<b>Maximum Surge Current (50/60Hz, 1 Cycle) [Apk]</b>	239/250	597/625	1670/1750
<b>Maximum On-State Voltage Drop @ Rated Current [Vpk]</b>	1.6	1.6	1.6
<b>Thermal Resistance Junction to Case (Rjc) [°C/W]</b>	1.02	0.63	0.22
<b>Maximum I<sup>2</sup> t for Fusing (50/60Hz, 1/2 cycle) [A<sup>2</sup> sec]</b>	285/259	1779/1621	13950/12709
<b>Minimum Power Factor (with Maximum Load)</b>	0.5	0.5	0.5

## Input <sup>(1)</sup>




Description	CMD
Control Voltage Range	3-32 VDC
Maximum Reverse Voltage	32 VDC
Maximum Turn-On Voltage	3.0 VDC
Minimum Turn-On Voltage	1.0 VDC
Typical Input Current @ max turn-on voltage	30 mA <sup>(4)</sup>
Nominal Input Impedance [Ohms]	17 mA @ 5 VDC
Maximum Turn-On Time [msec]	1/2 Cycle
Maximum Turn-Off Time [msec]	1/2 Cycle

## General

Description	Parameters
Dielectric Strength, Input/Output (50/60Hz)	4000 Vrms
Minimum Insulation Resistance (@ 500 VDC)	10 <sup>9</sup> Ohms
Maximum Capacitance, Input/Output	8 pF
Ambient Operating Temperature Range	-40 to 80 °C
Ambient Storage Temperature Range	-40 to 125 °C
Status Indicator Display	Green LED
Weight (typical)	3.0 oz (86.5 g)
Encapsulation	Thermally Conductive Epoxy
Terminals	Cage Type
Maximum Wire Size-Output:	AWG 8 (3.8mm)
Maximum Wire Size-Input:	AWG 12 (2.5mm)
Recommended Terminal Screw Torque Range:	Output: 10-15 lb-in (1.1-1.7 Nm)
	Input: 5-6 lb-in (0.6-0.7 Nm)


## THERMAL DERATE INFORMATION

### Current Derating Curves




# MECHANICAL SPECIFICATIONS

\*Tolerances: ±0.02 in / 0.5 mm  
 All dimensions are in: inches [millimeters]



# AVAILABLE OPTIONS

Example : CMD4825



## GENERAL NOTES

- (1) All parameters at 25°C unless otherwise specified.
- (2) Off-State dv/dt test method per EIA/NARM standard RS-443, paragraph 13.11.1
- (3) HEAT SINKING REQUIRED, FOR DERATING curves see page 3.
- (4) Input circuitry incorporates active current limiter.

## AGENCY APPROVALS & CERTIFICATIONS

Designed in accordance with the requirements of IEC 62314



## WARNINGS



### RISK OF MATERIAL DAMAGE AND HOT ENCLOSURE

- The product's side panels may be hot, allow the product to cool before touching
- Follow proper mounting instructions including torque values
- Do not allow liquids or foreign objects to enter this product

**Failure to follow these instructions can result in serious injury, or equipment damage.**



### HAZARD OF ELECTRIC SHOCK, EXPLOSION OR ARC FLASH

- Disconnect all power before installing or working with this equipment
- Verify all connections and replace all covers before turning on power

**Failure to follow these instructions will result in death or serious injury.**

Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at [www.sensata.com](http://www.sensata.com) SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

## CONTACT US

### Americas

+1 (877) 502 5500  
sales.crydom@sensata.com  
**Europe, Middle East & Africa**  
+44 (1202) 416170  
ssr-info.eu@sensata.com

### Asia Pacific

sales.isasia@list.sensata.com  
China +86 (21) 2306 1500  
Japan +81 (45) 277 7117  
Korea +82 (31) 601 2004  
India +91 (80) 67920890  
Rest of Asia +886 (2) 27602006  
ext 2808