

Part Number : 2243572216

Product Description : SW1-to-Pigtail Off-the-Shelf (OTS) Cable Assembly, 6.00mm Diameter, Female, 1000.00mm Length, 2 AWG, Red Status : Active

Series Number : 224357 Product Category : Power and Signal Cable Assemblies

Documents & Resources

Drawings

Drawing 2243572216_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | ø |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2023)8585-DC (23 Jan 2024) |
| EU RoHS | Not Reviewed per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|------------------------|---|
| Category | Power and Signal Cable Assemblies |
| Series | 224357 |
| Description | SW1-to-Pigtail Off-the-Shelf (OTS) Cable Assembly, 6.00mm Diameter, Female, 1000.00mm Length, 2 AWG, Red |
| Application | Power, Wire-to-Busbar, Wire-to- Board |
| Assembly Configuration | Single Ended Connector |
| Connector to Connector | SW1 6.00mm-to-Pigtail |
| Product Family | SW1 Connectors |
| Product Name | SW1 |
| Туре | Discrete Wire Assembly |
| UPC | 196823528620 |

Electrical

| Current - Maximum per Contact | 120.0A |
|-------------------------------|--------|
| Voltage - Maximum | 1000V |

Physical

| Cable Length | 1000.00mm |
|--------------------------------|----------------|
| Circuits (Loaded) | 1 |
| Circuits (maximum) | 1 |
| Color - Resin | Red |
| Gender | Female-Pigtail |
| Lock to Mating Part | Yes |
| Material - Metal | Copper Alloy |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Silver |
| Material - Resin | PBT |
| Net Weight | 448.991/g |
| Number of Rows | 1 |
| Overmolded | No |
| Packaging Type | Bag |

| Single Ended | Yes |
|-----------------------------|----------------------|
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type | UL 1015 |
| Wire Insulation Diameter | 12.00mm |
| Wire Size (AWG) | 2 |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|--|---------------|
| SW1 6.00mm Knurled Press-fit Locking Pins | <u>218335</u> |
| SW1 6.00mm Screw Mount Locking Pins | <u>218371</u> |

This document was generated on Apr 13, 2024