



Part Number : [2043160006](#)

Series Number : 204316

Product Category : PCB Headers and Receptacles

Product Description : Sentrality 6.00mm Top-entry, Knurled Press-fit Socket Assembly, Tray

Status : Active

Documents & Resources

Drawings

[Drawing 2043160006_sd.pdf](#)

[Packaging Design Drawing 2043180006-PK-000.pdf](#)

3D Models and Design Files

[3D Model 2043160006_stp.zip](#)

Specifications

[Application Specification 2043130006-AS-000.pdf](#)


[Product Specification 2043130006-PS-000.pdf](#)

[Test Summary 2043130006-TS-000.pdf](#)

[Test Summary 2043131234-TS-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	PCB Headers and Receptacles
Series	204316
Description	Sentrality 6.00mm Top-entry, Knurled Press-fit Socket Assembly, Tray
Application	Busbar-to-Board, Busbar-to- Busbar, Power
Comments	Current and voltage performances are dependent upon application variables.
Component Type	PCB Receptacle
Product Family	Sentrality Pin and Socket Interconnect System
Product Name	Sentrality
UPC	191130149919

Electrical

Current - Maximum per Contact	140.0A
Voltage - Maximum	600V

Physical

Circuits (Loaded)	1
Circuits (maximum)	1
Diameter	6.00mm
Durability (mating cycles max)	200
Glow-Wire Capable	No
Guide to Mating Part	No
Height Above Board	4.00mm
Material - Metal	Copper Alloy

Material - Plating Mating	Gold
Material - Plating Termination	Silver
Mating Orientation	Top-entry
Net Weight	6.521/g
Number of Rows	1
Orientation	Vertical
Packaging Type	Tray
PCB Retention	None
Pitch - Mating Interface	N/A
Polarized to PCB	No
Temperature Range - Operating	-40° to +125°C
Termination Interface Style	Press-Fit

Mates With / Use With

Mates with Part(s)

Description	Part Number
Sentrality Pins	<u>203263</u>