

Part Number: 2141320001

**Product Description :** Sentrality 3.4mm Topentry, Eye-of-Needle Press-fit Socket

Assembly with +/- 1.00mm Self-alignment

Capability, Tray **Status:** Active

Series Number: 214132

**Product Category: PCB Headers and** 

Receptacles

#### **Documents & Resources**

#### **Drawings**

Drawing 2141320001\_sd.pdf Packaging Design Drawing 2141320000-PK-000.pdf

### 3D Models and Design Files

3D Model 2141320001\_stp.zip

#### **Specifications**

Application Specification 2151130000-AS-000.pdf Product Specification 2151130000-PS-000.pdf Test Summary 2043131234-TS-000.pdf

### **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

### **Part Details**

### General

Status	Active
Category	PCB Headers and Receptacles
Series	214132
Description	Sentrality 3.4mm Top-entry, Eye-of- Needle Press-fit Socket Assembly with +/- 1.00mm Self-alignment Capability, Tray
Application	Board-to-Board, Busbar-to-Board, Power
Comments	Current and voltage performances are dependent upon application variables.
Component Type	PCB Receptacle
Product Family	Sentrality Pin and Socket Interconnect System
Product Name	Sentrality
UPC	195842227514

# Agency

### **Electrical**

Current - Maximum per Contact	75.0A
Voltage - Maximum	600V

# Physical

Circuits (Loaded)	1
Circuits (maximum)	1
Diameter	3.40mm
Durability (mating cycles max)	200

Flammability	94V-0
Glow-Wire Capable	No
Guide to Mating Part	Yes
Height Above Board	11.84mm
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Silver
Mating Orientation	Top-entry
Net Weight	10.612/g
Number of Rows	1
Orientation	Vertical
Packaging Type	Tray
PCB Retention	None
Pitch - Mating Interface	N/A
Polarized to PCB	No
Temperature Range - Operating	-40° to +125°C
Termination Interface Style	Through Hole - Compliant Pin

## Mates With / Use With

## Mates with Part(s)

Description	Part Number
Sentrality Pins	<u>203263</u>

This document was generated on Apr 15, 2024