

WBC-CH-6OR-BK-25-0023**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Battery storage systems are playing an increasingly important role in the field of renewable energies. They usually consist of several individual batteries that need to be quick and easy to replace. The Weidmüller Battery Connector (WBC) makes it possible to connect several individual batteries to an ESS in just a few simple steps – and to disconnect the connections just as quickly if required. For more safety and easy handling, the poles are clearly marked: The positive pole in orange and the negative pole in black.

General ordering data

Order No.	2938270000
Type	WBC-CH-6OR-BK-25-0023
GTIN (EAN)	4099986699120
Qty.	1 pc(s).

WBC-CH-60R-BK-25-0023

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 120 g

Temperatures

Continuous operating temp., min. -40 °C Continuous operating temp., max. 125 °C

General Data

Approvals	UL 4128	Colour	black, orange
Conductor cross-section, max.	25 mm ²	Contact diameter, male Ø	6 mm
Outer cable diameter, max.	6 mm	Surface finish	silver
Type	Female		

Technical Data

Plugging cycles	≥ 100	Protection degree	IP67 plugged
Rated current	120 A	Rated voltage	1,500 V

Classifications

ETIM 6.0	EC002928	ETIM 7.0	EC002928
ETIM 8.0	EC002928	ETIM 9.0	EC002928
ECLASS 9.0	22-57-92-03	ECLASS 9.1	27-44-01-07
ECLASS 10.0	27-44-01-07	ECLASS 11.0	22-57-02-92
ECLASS 12.0	22-57-02-92	ECLASS 13.0	22570292

Approvals

ROHS Conform

Downloads

Catalogues [Catalogues in PDF-format](#)

WBC-CH-60R-BK-25-0023

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

