



Part Number : 761501026

Product Description : Impact 100 Ohm 6 Pair
Right-Angle Daughtercard Receptacle,
Unguided, 16 Columns, 288 Circuits, Plated
Through Hole Dimension 0.39mm, Lead-Free

Series Number : 76150

Status : Active

Product Category : Backplane Connectors

Documents & Resources

Drawings

Drawing 761501026_sd.pdf

Packaging Design Drawing PK-70873-589-001.pdf

3D Models and Design Files

3D Model 761501026_stp.zip

Electrical Model Document EE-76150-001-002.pdf

Electrical Model Document EE-76560-0001-001.pdf

S-Parameter Model SP-76150-001-002.zip

S-Parameter Model SP-76560-0001-001.zip

Symbol Footprint Data SYM-76150-1026-001.zip

Specifications

Application Specification AS-76060-990-001.pdf

Application Specification AS-76060-9999-001.pdf

Product Specification PS-45499-002-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC

- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Backplane Connectors
Series	76150
Description	Impact 100 Ohm 6 Pair Right-Angle Daughtercard Receptacle, Unguided, 16 Columns, 288 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free
Application	Conventional, Coplanar, Daughtercard
Component Type	PCB Receptacle
Product Family	Impact Backplane Connector and Cable Assembly System
Product Name	Impact
UPC	883906217112

Agency

UL	E29179
----	--------

Electrical

Current - Maximum per Contact	0.75A
Data Rate	25.0 Gbps
Impedance	100Ω
Shield Type	N/A
Shielded	No
Voltage - Maximum	30V AC (RMS)/DC

Physical

Circuits (Loaded)	288
Circuits (maximum)	288
Color - Resin	Black
Durability (mating cycles max)	200
First Mate / Last Break	No
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	None
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	36.207/g
Number of Columns	16
Number of Pairs	6
Number of Rows	18
Orientation	Right Angle
Packaging Type	Tray
PC Tail Length	1.20mm
PCB Locator	No
PCB Retention	None
PCB Thickness - Recommended	1.00mm
Pitch - Mating Interface	1.90mm
Pitch - Termination Interface	1.90mm
Plating min - Mating	0.762µm
Polarized to PCB	No
Stackable	No
Temperature Range - Operating	-55° to +85°C
Termination Interface Style	Through Hole - Compliant Pin

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

Mates With / Use With

Mates with Part(s)

Description	Part Number
Impact 100 Ohm 6 Pair Vertical Backplane Headers	<u>76145</u>

Use with Part(s)

Description	Part Number
Wide Guide Modules and Pins	<u>76153</u>

This document was generated on Apr 15, 2024
