



Part Number : [761601038](#)

**Product Description :** Impact 100 Ohm 4 Pair Right-Angle Daughtercard Receptacle, Unguided, 8 Columns, 96 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free

Series Number : 76160

Status : Active

Product Category : Backplane Connectors

---

## Documents & Resources

### Drawings

[Drawing 761601038\\_sd.pdf](#)

[Packaging Design Drawing PK-70873-610-001.pdf](#)

### 3D Models and Design Files

[3D Model 761601038\\_stp.zip](#)

[Electrical Model Document EE-76160-003-001.pdf](#)

[S-Parameter Model SP-76160-003-001.zip](#)

[Symbol Footprint Data SYM-76160-1038-001.zip](#)

### Specifications

[Application Specification AS-76060-990-001.pdf](#)

[Application Specification AS-76060-9999-001.pdf](#)


[Product Specification PS-45499-002-001.pdf](#)

[Test Summary TS-76160-0001-001.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

---

### Part Details

#### General

Status	Active
Category	Backplane Connectors
Series	76160
Description	Impact 100 Ohm 4 Pair Right-Angle Daughtercard Receptacle, Unguided, 8 Columns, 96 Circuits, Plated Through Hole Dimension 0.39mm, Lead-Free
Application	Conventional, Coplanar, Daughtercard
Component Type	PCB Receptacle
Product Family	Impact Backplane Connector and Cable Assembly System
Product Name	Impact
UPC	883906156732

#### Agency

UL	E29179
----	--------

#### Electrical

Current - Maximum per Contact	0.75A
Data Rate	25.0 Gbps
Impedance	100Ω
Shield Type	N/A
Shielded	No
Voltage - Maximum	30V AC (RMS)/DC

#### Physical

Circuits (Loaded)	96
Circuits (maximum)	96
Color - Resin	Black
Durability (mating cycles max)	200
First Mate / Last Break	No
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	None
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	10.339/g
Number of Columns	8
Number of Pairs	4
Number of Rows	12
Orientation	Right Angle
Packaging Type	Tray
PC Tail Length	1.20mm
PCB Locator	No
PCB Retention	None
PCB Thickness - Recommended	1.00mm
Pitch - Mating Interface	1.90mm
Pitch - Termination Interface	1.90mm
Plating min - Mating	0.762µm
Polarized to PCB	No
Stackable	No
Temperature Range - Operating	-55° to +85°C
Termination Interface Style	Through Hole - Compliant Pin

#### Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

---

#### Mates With / Use With

### Mates with Part(s)

Description	Part Number
Impact 100 Ohm 4 Pair Vertical Backplane Headers	<u>76155</u>
Impact 100 Ohm 4 Pair RAM Right-Angle Headers	<u>76500</u>

### Use with Part(s)

Description	Part Number
Wide Guide Modules and Pins	<u>76153</u>

---

This document was generated on Apr 15, 2024