

Part Number: 1714001026

Product Description : Impel 90 Ohm, 6 Pair Right-Angle Daughtercard, 1.90mm Pitch, Unguided, 16 Columns, 192 Circuits, Plated

Through Hole Dimension 0.36mm

Status: Active

Series Number: 171400

Product Category: Backplane Connectors

Documents & Resources

Drawings

<u>Drawing 1714001026_sd.pdf</u> Packaging Design Drawing PK-78888-088-001.pdf

3D Models and Design Files

3D Model 1714001026_stp.zip
Electrical Model Document 1714002001A-000.pdf
Electrical Model Document 1714002002-000.pdf
S-Parameter Model 1714002001-SP-000.zip
S-Parameter Model 1714002002-000.zip
Symbol Footprint Data SYM-171400-1026-001.zip

Specifications

Application Specification 1713209994-AS-000.pdf
Application Specification AS-171320-990-001.pdf
Application Specification AS-171320-991-001.pdf
Application Specification AS-171320-992-001.pdf
Product Specification PS-171320-999-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	©
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Backplane Connectors
Series	171400
Description	Impel 90 Ohm, 6 Pair Right-Angle Daughtercard, 1.90mm Pitch, Unguided, 16 Columns, 192 Circuits, Plated Through Hole Dimension 0.36mm
Application	Coplanar, Daughtercard
Component Type	PCB Receptacle
Product Family	Impel and Impel Plus Backplane Solutions
Product Name	Impel
UPC	887191080666

Agency

Electrical

Current - Maximum per Contact	0.75A
Data Rate	40.0 Gbps
Impedance	90Ω
Shield Type	Full Shield
Voltage - Maximum	29.9V AC (RMS)/DC

Physical

Circuite (Leaded)	103
Circuits (Loaded)	192
Circuits (maximum)	192
Color - Resin	Black
Durability (mating cycles max)	200
First Mate / Last Break	No
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	None
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Gold
Material - Plating Termination	Nickel, Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	78.106/g
Number of Columns	16
Number of Pairs	6
Number of Rows	12
Orientation	Right Angle
Packaging Type	Tray
PC Tail Length	1.30mm
PCB Locator	No
PCB Retention	None
PCB Thickness - Recommended	1.00mm
Pitch - Mating Interface	1.90mm
Pitch - Termination Interface	1.90mm
Plating min - Mating	0.762µm
Temperature Range - Operating	-55° to +85°C

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

Mates With / Use With

Mates with Part(s)

Description	Part Number
Impel 90 Ohm, 6 Pair Vertical Backplane Header, 1.90mm Pitch, Unguided, Open Endwalls, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.46mm	<u>1713951605</u>
Impel 90 Ohm, 6 Pair Vertical Backplane Header, 1.90mm Pitch, Unguided, Open Endwalls, 16 Columns, 192 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.36mm	<u>1713951607</u>
Impel 90 Ohm, 6 Pair Vertical Backplane Header, 1.90mm Pitch, Unguided, Open Endwalls, 16 Columns, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.36mm	<u>1713951608</u>
Impel 90 Ohm 6 Pair Right-Angle Header, 1.90mm Pitch, Unguided, 16 Columns, Open Endwalls, 192 Circuits, Pin Length 5.50mm, Plated Through Hole Dimension 0.36mm	<u>1721301608</u>

This document was generated on Apr 09, 2024