

5-6450860-0 ✓ ACTIVE

MULTI-BEAM | MULTI-BEAM XLE

TE Internal #: 5-6450860-0

Rectangular Power Connectors, Connector Assembly, Receptacle, Board-to-Board, 32 Position, 2.54 mm [.1 in] Centerline, MULTI-BEAM XLE

[View on TE.com >](#)



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Connector Assembly**

Connector & Housing Type: **Receptacle**

Connector System: **Board-to-Board**

Number of Positions: **32**

Centerline (Pitch): **2.54 mm [.1 in]**

## Features

### Product Type Features

Assembly Requirement	Factory Assembled
Rectangular Power Connector Type	Connector Assembly
Connector & Housing Type	Receptacle
Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board

### Configuration Features

Mating & Unmating Configuration	Normal
Number of Positions	32
PCB Mount Orientation	Vertical
Number of Power Positions	8
Number of Signal Positions	24
Number of Rows	4

### Electrical Characteristics

Operating Voltage	60 VDC
-------------------	--------

### Body Features

Wire Color (Base)	Black
-------------------	-------

### Contact Features

Power Contact Base Material	Tin
-----------------------------	-----



Contact Underplating Material Thickness	3.43 $\mu$ m
---	--------------

Contact Mating Area Plating Material	Gold
--------------------------------------	------

Contact Underplating Material	Nickel
-------------------------------	--------

Contact Current Rating (Max)	42 A
------------------------------	------

Contact Retention Within Housing	Without
----------------------------------	---------

Contact Type	Receptacle
--------------	------------

PCB Contact Termination Area Plating Material	Tin
---	-----

Contact Mating Area Plating Material Thickness	.076 $\mu$ m[3 $\mu$ in]
--	--------------------------

### Termination Features

Termination Post & Tail Length	3.43 mm[.135 in]
--------------------------------	------------------

Termination Method to Printed Circuit Board	Through Hole - Press-Fit
---	--------------------------

### Mechanical Attachment

PCB Mount Retention	With
---------------------	------

PCB Mount Retention Type	Boardlock
--------------------------	-----------

Mating Retention Type	Boardlock
-----------------------	-----------

Connector Mounting Type	Board Mount
-------------------------	-------------

### Housing Features

Centerline (Pitch)	2.54 mm[.1 in]
--------------------	----------------

Housing Color	Black
---------------	-------

Housing Material	High Temperature Thermoplastic
------------------	--------------------------------

### Dimensions

Row-to-Row Spacing	2.54 mm[.1 in]
--------------------	----------------

### Usage Conditions

Operating Temperature Range	-40 - 125 $^{\circ}$ C[-40 - 257 $^{\circ}$ F]
-----------------------------	--

### Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

### Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Glow Wire Rating	High Temperature Part - Not Glow Wire
------------------	---------------------------------------

### Packaging Features

Packaging Method	Tray
------------------	------



## Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

## Compatible Parts



Also in the Series | **MULTI-BEAM XLE**




Rectangular Power Connectors(111)

## Customers Also Bought



TE Part # 1658871-1  
XFP CAGE ASSY W/ INSULATING TA



TE Part # 5084618-2  
0.8FH,R13H.5,060,30/Sn,TR,SC



TE Part # 2013499-1  
MICRO USB, TYPE B



TE Part # 1-5406299-1  
MJ ASSY,S/P,8POS,SH,RVPGT,CAT5



TE Part # 5569381-1  
STK MJ ASSY,8POS,2X1,SHLD,CAT5



TE Part # 1-2170704-3  
CAGE ASSY, QSFP28 1X1, SPRING, CZ\_HS



TE Part # 1-2306755-3  
ZQSFP HEATSINK,



TE Part # 2316821-8  
SFP+assy2x1 Spring Fingers No Lp Sn



TE Part # 2306003-1  
HEAT SINK CLIP, STRADDLE QSFP28 1XN

## Documents

### Product Drawings

[MBXLE VERT RCPT 3HDP+1LP+24S+1LP+3HDP](#)

English

### CAD Files

[3D PDF](#)

[3D](#)

### Customer View Model

[ENG\\_CVM\\_CVM\\_5-6450860-0\\_J.2d\\_dxf.zip](#)



English

**Customer View Model**

[ENG\\_CVM\\_CVM\\_5-6450860-0\\_J.3d\\_igs.zip](#)

English

**Customer View Model**

[ENG\\_CVM\\_CVM\\_5-6450860-0\\_J.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

---

**Product Specifications**

[Application Specification](#)

English

---

**Agency Approvals**

[UL Report](#)

English