

XVGB2W

Monolithic tower lights, Harmony XVG, 60mm, red green, steady light, base mounting, IP53, 24V AC/DC



Main

Range of Product	Harmony XVG
Product or Component Type	Complete pre-wired monolithic tower light
Beacon or indicator bank unit type	2 illuminated units
Material	PC (UL94 V-2): globe ABS (UL94HB): tube body Aluminium: tube
Mounting diameter	2.36 in (60 mm)
Component name	XVG
Device mounting	Base mounting
Light source	LED steady red LED steady green
Light block color	Red/green
Indicator bank base type	Base without buzzer

Complementary

Rated supply voltage	24 V AC/DC
Cable cross section	0.00 in ² (0.33 mm ²)
Discrete output type	PNP and NPN
[Uimp] rated impulse withstand voltage	0.5 kV
Current Consumption	68 mA
Power Consumption in W	1.6 W
Fundamental frequency	2.64 kHz
Net Weight	0.44 lb(US) (0.2 kg)

Environment

Product Certifications	CE[RETURN]EAC
Ambient Air Temperature for Storage	-31...158 °F (-35...70 °C)
Ambient Air Temperature for Operation	14...122 °F (-10...50 °C)
IP Degree of Protection	IP53

Ordering and shipping details

Category	US1CP4B22153
Discount Schedule	CP4B
GTIN	3606480390210
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.20 in (31.0 cm)
Package 1 Width	3.35 in (8.5 cm)
Package 1 Length	2.95 in (7.5 cm)
Package 1 Weight	10.83 oz (307.0 g)
Unit Type of Package 2	S04
Number of Units in Package 2	21
Package 2 Height	11.81 in (30 cm)
Package 2 Width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)
Package 2 Weight	16.64 lb(US) (7.55 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	84
Package 3 Height	29.53 in (75 cm)
Package 3 Width	23.62 in (60 cm)
Package 3 Length	31.50 in (80 cm)
Package 3 Weight	83.78 lb(US) (38 kg)


Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information


Contractual warranty

Warranty	18 months
----------	-----------


Dimensions



Mounting



Wiring



(1) "ON" for lighting and/or applying continuous sound.

(2) Fuse (rated current: 0.5 A)

RD : Red

GR : Green

BK : Black