




MUS38-20-20-F

Ruland MUS38-20-20-F, 20mm x 20mm Single Universal Joint, Friction Bearing, Steel, 38.0mm OD, 82.0mm Length




Description

Ruland MUS38-20-20-F is a single cardan friction bearing universal joint with 20mm x 20mm bores, 38.0mm OD, and 82.0mm length. It is ideal for applications with space constraints and has higher torque capacity than equivalently sized double universal joints. This plain bearing universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 45° when compared to commodity style single universal joints. MUS38-20-20-F is made from high grade alloy steel for durability and high strength. It can be combined with boot UBOOT24/38-NI-KIT to protect the joint from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This single cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

Bore (B1)	20 mm	Small Bore (B2)	20 mm
B1 Max Shaft Penetration	22.6 mm	B2 Max Shaft Penetration	22.6 mm
Joint Outer Diameter (OD)	38.0 mm	Bore Tolerance	+0.021 mm / -0.000 mm
Length (L)	82.0 mm	Yoke Length (LY)	41.0 mm
Hub Depth (LH)	22.6 mm	Rated Torque	226.0 Nm
Max Operating Angle	45°	Material Specification	Alloy Steel
Manufacturer	Belden Universal	Country of Origin	USA
Weight (lbs)	1.112000	Recommended Lubricant	LUBRIPLATE No. 1200-2
UPC	634529287743	Tariff Code	8483.60.4000
UNSPC	25173810		

Note 1 Performance ratings are for guidance only. The user must determine suitability for a particular application.

Prop 65  **WARNING** This product can expose you to the chemical Ethylene Thiourea, known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.