

CATALOG NUMBER

PVT11500R



CERTIFICATIONS



FEATURES

Uniquely designed for protection of centralized solar inverters on the DC input side and string boxes

Thermal protection included to ensure safe failure modes

Compact, yet high surge rated pluggable design, using minimum DIN rail width

PRODUCT ATTRIBUTES

Max Continuous Operating Voltage (Ucpv): 1500

Nominal Discharge Current (In), IEC: 20 kA 8/20 µs

Impulse Current (Iimp): 5 kA 10/350 µs

Total Discharge Current (Itotal): 10 kA 10/350 -s; 40 kA 8/20 -s

Voltage Protection Level (Up): 5000 V

Response Time: 25 ns max

Short Circuit Current Rating (Iscrr): 11 kA

Max Continuous Operating Voltage (Vpvc): 1,500 VDC

Voltage Protection Rating (VPR): 4000 V

Nominal Discharge Current (In), UL: 20 kA 8/20 µs

Short Circuit Current Rating (SCCR): 65 kA

Protection Modes: -ve to PE; -ve to +ve; +ve to PE

Altitude: 6562' max

Humidity: 5 – 95

Temperature: -40 to 185 °F

Connection, Flexible: #4

Connection, Solid: #2

Connection, Stranded: #2

Enclosure Material: UL® 94V-0 Thermoplastic

Enclosure Rating: IP 20

Mounting: 35 mm top hat DIN rail

Torque (TQ): 3.3'·lbf max

Remote Contact Switching Capacity: 1 A @ 125 VAC A; 1 A @ 250 VAC A; 0.5 A @ 12 VDC A; 0.5 A @ 24 VDC A; 0.5 A @ 48 VDC A

Remote Contacts: Yes

Status Indication: Mechanical flag

Depth (D): 3.35"

Height (H): 3.54"

Width (W): 2.13"


Unit Weight: 1.1 lb

Replacement Module: PVT1750M; PVT1750SM

Certification Details: UL® 1449 Edition 4 Type 1CA

Complies With: EN IEC 61643-31, Type 1, Type 2

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER