

## CATALOG NUMBER

**PVT21500R**



## CERTIFICATIONS



## FEATURES

- Suited for use at the DC input of distributed string inverters in solar arrays
- Thermal protection included to ensure safe failure modes
- Compact, yet high surge rated pluggable design, using minimum DIN rail width

## PRODUCT ATTRIBUTES

- Max Continuous Operating Voltage (Ucpv): 1500
- Nominal Discharge Current (In), IEC: 20 kA 8/20  $\mu$ s
- Max Discharge Current (Imax): 30 kA 8/20  $\mu$ s
- Total Discharge Current (Itotal): 40 kA 8/20 -s
- Voltage Protection Level (Up): 5000 V
- Response Time: 25 ns Max
- Short Circuit Current Rating (Iscrr): 11 kA
- Max Continuous Operating Voltage (Vpvc): 1,500 VDC
- Voltage Protection Rating (VPR): 4000 V
- Nominal Discharge Current (In), UL: 20 kA 8/20  $\mu$ s
- Short Circuit Current Rating (SCCR): 65 kA
- Protection Modes: -ve to PE;-ve to +ve;+ve to PE
- Altitude: 6562' Max

Humidity: 5 – 95

Temperature: -40 to 185 °F

Connection, Flexible: #4

Connection, Solid: #2

Connection, Stranded: #2

Enclosure Material: UL® 94V-0 Thermoplastic

Enclosure Rating: IP 20

Mounting: 35 mm top hat DIN rail

Torque (TQ): 3.3'·lbf Max

Remote Contact Switching Capacity: 1 A @ 125 VAC A; 1 A @ 250 VAC A; 0.5 A @ 12 VDC A; 0.5 A @ 24 VDC A; 0.5 A @ 48 VDC A

Remote Contacts: Yes

Status Indication: Mechanical flag

Depth (D): 2.72"

Height (H): 3.54"

Width (W): 2.13"


Unit Weight: 1 lb

Replacement Module: PVT2750M

Certification Details: UL® 1449 Edition 4 Type 1CA

Complies With: EN 50539-11 Type 1, Type 2

## DIAGRAMS



## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

**North America**  
+1.800.753.9221  
Option 1 – Customer Care  
Option 2 – Technical Support

**Europe**  
Netherlands:  
+31 800-0200135  
France:  
+33 800 901 793

**Europe**  
Germany:  
800 1890272  
Other Countries:  
+31 13 5835404

**APAC**  
Shanghai:  
+ 86 21 2412 1618/19  
Sydney:  
+61 2 9751 8500



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**