

2891453

https://www.phoenixcontact.com/us/products/2891453

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ethernet switch, 4 TP RJ45 ports, 1 FO port, 100 Mbps full duplex in ST-D format, automatic detection of data transmission speed of 10 or 100 Mbps (RJ45), autocrossing function

Your advantages

- RJ45 ports support a transmission speed of 10/100 Mbps
- Fiber-optic ports support 100 Mbps
- · QoS-prioritized (Quality of Service) messages
- · Local diagnostic indicators with LEDs
- · The switch also offers cable locking and port blocking
- · Auto negotiation and autocrossing detection simplifies installation and setup

Commercial data

Item number	2891453
Packing unit	1 pc
Sales key	DN19
Product key	DNN113
Catalog page	Page 291 (C-6-2019)
GTIN	4046356100816
Weight per piece (including packing)	291.5 g
Weight per piece (excluding packing)	265 g
Customs tariff number	85176200
Country of origin	TW



2891453

https://www.phoenixcontact.com/us/products/2891453

Technical data

Dimensions

Width	30 mm
Height	131 mm
Depth	70 mm

Material specifications

H2 (-2-)	Al'.
Housing material	Aluminum

Mounting

	5 11 11 11
Mounting type	DIN rail mounting

Interfaces

Ethernet (RJ45)

,	
Connection method	RJ45
Note on the connection method	Auto negotiation and autocrossing
Transmission speed	10/100 Mbps
Transmission physics	Ethernet in RJ45 twisted pair
Transmission length	100 m (per segment)
Signal LEDs	Data receive, link status
No. of channels	4 (RJ45 ports)

Fiber optic interface

Connection method	ST
Transmission speed	100 Mbps (full duplex)
Transmission physics	multi-mode fiberglass
Transmission length	2000 m (Fiberglass 50/125)
	2000 m (Fiberglass 62.5/125)
Wavelength	1300 nm
No. of channels	1 (ST multi-mode)

Product properties

Product type	Switch
Product family	Unmanaged Switch SFN
Туре	Block design
MTTF	193 Years (MIL-HDBK-217F standard, temperature 25°C, operating cycle 100%)

Insulation characteristics

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
------------------	---------------------------------------

Switch functions

Basic functions	Unmanaged switch / auto negotiation, complies with IEEE 802.3,
	store and forward switching mode



2891453

https://www.phoenixcontact.com/us/products/2891453

Status and diagnostic indicators	LEDs: U _S , link and activity per port
Additional functions	Autonegotiation
ecurity functions	
Basic functions	Unmanaged switch / auto negotiation, complies with IEEE 802.3 store and forward switching mode
ctrical properties	
Local diagnostics	US Supply voltage Green LED
	LNK/ACT Link status/data transmission Green LED
	100 Data transmission speed Yellow LED
Maximum power dissipation for nominal condition	3.36 W
Test section	500 V DC 1 min.
Transmission medium	Copper
	FO
upply	
Supply voltage (DC)	24 V DC
Supply voltage range	9 V DC 32 V DC
Residual ripple	3.6 V _{PP} (within the permitted voltage range)
Typical current consumption	140 mA (at U _S = 24 V DC)
nnection data	
connection technology	
Connection name	Power supply
pluggable	yes

Environmental and real-life conditions

Ambient conditions

Stripping length

Connection method

Conductor cross section, rigid

Conductor cross section AWG

Conductor cross section, flexible

Degree of protection	IP20
Ambient temperature (operation)	0 °C 60 °C
Ambient temperature (storage/transport)	-20 °C 70 °C
Permissible humidity (operation)	5 % 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % 95 % (non-condensing)
Vibration (operation)	in acc. with IEC 60068-2-6: 5g, 150 Hz
Air pressure (operation)	86 kPa 108 kPa (up to 1500 m above sea level)
Air pressure (storage/transport)	66 kPa 108 kPa (up to 3500 m above sea level)

Screw connection

0.2 mm² ... 2.5 mm²

0.2 mm² ... 2.5 mm²

24 ... 12

7 mm



2891453

https://www.phoenixcontact.com/us/products/2891453

Resistance to gases that may endanger the functions, in acc. with DIN 40046-36, DIN 40046-37	Sulfur dioxide (SO ₂) 10 \pm 0.3 cm ³ /m ³ , hydrogen sulfide (H ₂ S) 1 \pm 0.3 cm ³ /m ³ , at 25°C and 75% humidity and exposure of four days
EMC data	
Noise immunity	EN 61000-6-2:2005
Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Noise emission	EN 61000-6-4
System properties Functionality	
Basic functions	Unmanaged switch / auto negotiation, complies with IEEE 802.3, store and forward switching mode
Signaling	
Status display	LEDs: U _s , link and activity per port



2891453

https://www.phoenixcontact.com/us/products/2891453

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2891453



EAC

Approval ID: RU*-DE.*.B.00741/19



UL Listed

Approval ID: FILE E 140324



cUL Listed

Approval ID: FILE E 140324



KC

Approval ID: MSIP-REI-PCK-2891453



cUL Listed

Approval ID: FILE E 199827



UL Listed

Approval ID: FILE E 199827

cULus Listed

cULus Listed



2891453

https://www.phoenixcontact.com/us/products/2891453

Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	19170402	
	ECLASS-12.0	19170402	
	ECLASS-13.0	19170402	
ETIM			
	ETIM 9.0	EC000734	
UNSPSC			

43222600



2891453

https://www.phoenixcontact.com/us/products/2891453

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c), 7(a), 7(c)-l
China RoHS	
Environment friendly use period (EFUP)	EFUP-10
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)



2891453

https://www.phoenixcontact.com/us/products/2891453

Accessories

MSTB 2,5/4-ST - PCB connector

1754481

https://www.phoenixcontact.com/us/products/1754481



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, contact connection type: Socket, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: MSTB 2,5/..-ST, pitch: 5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

DT-LAN-CAT.6+ - Surge protection device

2881007

https://www.phoenixcontact.com/us/products/2881007



Surge protection in accordance with Class E_A (CAT6_A), for Gigabit Ethernet (up to 10 Gbps), token ring, FDDI/CDDI, ISDN, and DS1. Suitable for Power over Ethernet (PoE++ / 4PPoE) "Mode A" and "Mode B". RJ45 attachment plug with separate grounding cable and ground connection snap-on foot for NS 35 DIN rails.



2891453

https://www.phoenixcontact.com/us/products/2891453

FL SEC PAC 4TX - Port Guard Security Element

2832865

https://www.phoenixcontact.com/us/products/2832865

Layer1 security elements for 4 RJ45 network connections for use with patch boxes and panels



FL DIN RA - DIN rail adapter

2891053

https://www.phoenixcontact.com/us/products/2891053

The FL DIN RA is installed in a standard, 19-inch rack (EIA-310-D, IEC 60297-3-100) to allow DIN rail mounted equipment to be rack mounted.





2891453

https://www.phoenixcontact.com/us/products/2891453

FL RJ45 PROTECT CAP - Dust protection

2832991

https://www.phoenixcontact.com/us/products/2832991



Dust protection caps for RJ45 socket

E/NS 35 N - End bracket

0800886

https://www.phoenixcontact.com/us/products/0800886



End clamp, width: 9.5 mm, color: gray



2891453

https://www.phoenixcontact.com/us/products/2891453

FL CAT5 PATCH 0,5 - Patch cable

2832263

https://www.phoenixcontact.com/us/products/2832263



Patch cable, CAT5, assembled, 0.5 m

FL CAT5 PATCH 1,0 - Patch cable

2832276

https://www.phoenixcontact.com/us/products/2832276



Patch cable, CAT5, assembled, 1 m



2891453

https://www.phoenixcontact.com/us/products/2891453

FL CAT5 PATCH 2,0 - Patch cable

2832289

https://www.phoenixcontact.com/us/products/2832289



Patch cable, CAT5, assembled, 2 m

NBC-R4AC-R4AC-IE8A/.../... - Patch cable

1411854

https://www.phoenixcontact.com/us/products/1411854



Patch cable, degree of protection: IP20, number of positions: 8, 10 Gbps, ${\rm CAT6}_{\rm A}$, cable outlet: straight, Ethernet



2891453

https://www.phoenixcontact.com/us/products/2891453

NBC-R4AC/10G-R4AC/10G-94F/2,0 - Patch cable

1408360

https://www.phoenixcontact.com/us/products/1408360



Patch cable, CAT6 $_{\rm A}$, 4-pair, shielded, connection not crossed (line), assembled at both ends with RJ45/IP20 connectors, outer sheath material: PUR, length: 2.0 $_{\rm m}$

NBC-R4AC/10G-R4AC/10G-94F/3,0 - Patch cable

1408365

https://www.phoenixcontact.com/us/products/1408365



Patch cable, CAT6 $_{\rm A}$, 4-pair, shielded, connection not crossed (line), assembled at both ends with RJ45/IP20 connectors, outer sheath material: PUR, length: 3.0 m



2891453

https://www.phoenixcontact.com/us/products/2891453

NBC-R4AC/1,0-93B/R4AC - Patch cable

1408968

https://www.phoenixcontact.com/us/products/1408968



Patch cable, degree of protection: IP20, cable length: 1 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET

NBC-R4AC/2,0-93B/R4AC - Patch cable

1408969

https://www.phoenixcontact.com/us/products/1408969



Patch cable, degree of protection: IP20, cable length: 2 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET



2891453

https://www.phoenixcontact.com/us/products/2891453

NBC-R4AC/5,0-93B/R4AC - Patch cable

1408970

https://www.phoenixcontact.com/us/products/1408970



Patch cable, degree of protection: IP20, cable length: 5 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET

FOC-ST:PA-SC:PA-OM2:D01/1 - FO patch cable

1115574

https://www.phoenixcontact.com/us/products/1115574

Multi-mode OM2 duplex jumper, ST-SC, UPC polishing, length 1 m





2891453

https://www.phoenixcontact.com/us/products/2891453

FOC-ST:PA-SC:PA-OM2:D01/2 - FO patch cable

1115573

https://www.phoenixcontact.com/us/products/1115573

Multi-mode OM2 duplex jumper, ST-SC, UPC polishing, length 2 $\rm m$



FOC-ST:PA-ST:PA-OM2:D01/1 - FO patch cable

1115560

https://www.phoenixcontact.com/us/products/1115560

Multi-mode OM2 duplex jumper, ST-ST, UPC polishing, length 1 m





2891453

https://www.phoenixcontact.com/us/products/2891453

FOC-ST:PA-ST:PA-OM2:D01/2 - FO patch cable

1115557

https://www.phoenixcontact.com/us/products/1115557

Multi-mode OM2 duplex jumper, ST-ST, UPC polishing, length 2 m



FOC-LC:PA-ST:PA-OM2:D01/1 - Fiber optic cable

1115588

https://www.phoenixcontact.com/us/products/1115588

Multi-mode OM2 duplex jumper, LC-ST, UPC polishing, length 1 m





2891453

https://www.phoenixcontact.com/us/products/2891453

FOC-LC:PA-ST:PA-OM2:D01/2 - Fiber optic cable

1115587

https://www.phoenixcontact.com/us/products/1115587

Multi-mode OM2 duplex jumper, LC-ST, UPC polishing, length 2 m



Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com