


SuperTan[®] Wet Tantalum Capacitors With Hermetic Seal, Extended Range, Improved Vibration Capability, 200 °C Applications



LINKS TO ADDITIONAL RESOURCES


[3D Models](#)

PERFORMANCE CHARACTERISTICS

Operating Temperature: -55 °C to +85 °C
(to +200 °C with voltage derating)

Capacitance Tolerance: at 120 Hz, +25 °C; ± 20 % standard; ± 10 %

DC Leakage Current (DCL Max.): at +25 °C and above: leakage current shall not exceed the values listed in the Standard Ratings tables.

Life Test: capacitors are capable of withstanding life test at 200 °C at the applicable derated DC working voltage.

FEATURES

- High capacitance, high performance (shock and vibration)
- Hermetically sealed, tantalum case
- +200 °C high temperature
- Terminations: axial, standard tin / lead (SnPb)
- 100 % tin (RoHS-compliant) available
- Mounting: through-hole
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS*
Available

**HALOGEN
FREE
GREEN
(5-2008)**
Available

Note

* This datasheet provides information about parts that are RoHS-compliant and / or parts that are non RoHS-compliant. For example, parts with lead (Pb) terminations are not RoHS-compliant. Please see the information / tables in this datasheet for details


APPLICATIONS

- Industrial
- Petroleum exploration
- High temperature / high stress environment

ORDERING INFORMATION								
T34	C	107	M	125	B	Z	6	S
MODEL	CASE CODE	CAPACITANCE	CAPACITANCE TOLERANCE	DC VOLTAGE RATING AT + 85 °C	TERMINATION AND PACKAGING	RELIABILITY LEVEL	CASE INSULATION	ESR
	See Standard Ratings table	This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow	K = ± 10 % M = ± 20 %	This is expressed in volts. To complete the three-digit block, zeros precede the voltage rating	A = 100 % tin (RoHS compliant), bulk B = std., tin / lead, bulk	Z = non-ER	8 = no outer case insulation 6 = high temperature insulation film	S = std. L = low

Note

- Packaging: the use of formed plastic trays for packing bulk components is standard

DIMENSIONS in inches [millimeters]


CASE CODE		D	L ₁ ⁽¹⁾	L ₂ (Max.)	E	WEIGHT (g) (Max.)
TYPE T34	CLR 79 / 81 EQUIV.					
A	T1	0.188 ± 0.016 [4.78 ± 0.41]	0.453 + 0.031 / - 0.016 [11.51 + 0.79 / - 0.41]	0.734 [18.64]	1.500 ± 0.250 [38.10 ± 6.35]	2.6
B	T2	0.281 ± 0.016 [7.14 ± 0.41]	0.641 + 0.031 / - 0.016 [16.28 + 0.79 / - 0.41]	0.922 [23.42]	2.250 ± 0.250 [57.15 ± 6.35]	6.2
C	T3	0.375 ± 0.016 [9.53 ± 0.41]	0.766 + 0.031 / - 0.016 [19.46 + 0.79 / - 0.41]	1.047 [26.59]	2.250 ± 0.250 [57.15 ± 6.35]	11.6
D	T4	0.375 ± 0.016 [9.53 ± 0.41]	1.062 + 0.031 / - 0.016 [26.97 + 0.79 / - 0.41]	1.343 [34.11]	2.250 ± 0.250 [57.15 ± 6.35]	17.7

Note

⁽¹⁾ For insulated parts, add 0.015 inches [0.38 mm] to the diameter. The insulation shall lap over the ends of the capacitor body

RATINGS AND CASE CODES

μF	50 V	60 V	75 V	100 V	125 V
10					A
15				A	
33			A	A	
47		A			B
68	A		A	B	
100					C
110			B		
150		B		B	D
220	B		B	D	
240					D
330			C		
350					D
390		C			
400				D	
470	C		D	D	
560		D		D	
680	D				
750			D	D	
1000		D	D		
1500	D				



STANDARD RATINGS									
CAPACITANCE AT 25 °C 120 Hz (µF)	V _{DC} AT 200 °C	CASE CODE	PART NUMBER	MAX. ESR 120 Hz (Ω)	MAX. DCL (µA) 25 °C	85 °C / 125 °C	AC RIPPLE 85 °C AT 40 kHz (mA _{RMS})	LIFE TEST PERFORMANCE (h AT +200 °C)	
50 V_{DC} AT +85 °C									
68	30	A	T34A686(1)050(2)(3)(4)S	2.5	2	10	1050	1000	
220	30	B	T34B227(1)050(2)(3)(4)S	0.9	4	20	1800	1000	
470	25	C	T34C477(1)050(2)(3)(4)S	0.75	3	25	2100	2000	
680	25	D	T34D687(1)050(2)(3)(4)S	0.7	5	7	2200	1000	
1500	25	D	T34D158(1)050(2)(3)(4)S	0.5	15	110	3000	500	
60 V_{DC} AT +85 °C									
47	36	A	T34A476(1)060(2)(3)(4)S	2.0	2	10	1050	1000	
150	36	B	T34B157(1)060(2)(3)(4)S	1.5	2	10	1650	1000	
390	30	C	T34C397(1)060(2)(3)(4)S	0.9	3	25	2100	1000	
560	36	D	T34D567(1)060(2)(3)(4)S	0.8	5	7	2500	1000	
1000	36	D	T34D108(1)060(2)(3)(4)S	0.7	20	90	3200	1000	
75 V_{DC} AT +85 °C									
33	45	A	T34A336(1)075(2)(3)(4)S	2.5	2	10	1050	2000	
68	45	A	T34A686(1)075(2)(3)(4)S	3.0	2	10	1050	500	
110	45	B	T34B117(1)075(2)(3)(4)S	1.3	2	10	1650	1000	
220	37	B	T34B227(1)075(2)(3)(4)S	1.8	5	50	2000	1000	
330	45	C	T34C337(1)075(2)(3)(4)S	1.0	3	25	2100	1500	
470	45	D	T34D477(1)075(2)(3)(4)S	0.9	5	50	2750	1000	
750	45	D	T34D757(1)075(2)(3)(4)S	0.7	25	150	3000	500	
1000	45	D	T34D108(1)075(2)(3)(4)S	0.7	20	90	3500	1000	
100 V_{DC} AT +85 °C									
15	60	A	T34A156(1)100(2)(3)(4)S	3.5	1	5	1050	1000	
33	60	A	T34A336(1)100(2)(3)(4)S	3.0	2	10	1050	2000	
68	60	B	T34B686(1)100(2)(3)(4)S	2.1	2	10	1650	1000	
150	50	B	T34B157(1)100(2)(3)(4)S	1.3	7.5	25	2100	1000	
220	60	D	T34D227(1)100(2)(3)(4)S	1.2	5	50	2750	1000	
400	60	D	T34D407(1)100(2)(3)(4)S	0.8	10	150	3000	1500	
470	60	D	T34D477(1)100(2)(3)(4)S	0.7	15	150	3000	1000	
560	60	D	T34D567(1)100(2)(3)(4)S	1.0	25	200	3000	1000	
750	50	D	T34D757(1)100(2)(3)(4)S	0.7	25	150	3000	500	
125 V_{DC} AT +85 °C									
10	75	A	T34A106(1)125(2)(3)(4)S	5.5	1	5	1050	1000	
47	75	B	T34B476(1)125(2)(3)(4)S	2.3	2	20	1650	1000	
100	75	C	T34C107(1)125(2)(3)(4)S	1.8	3	35	2100	1000	
150	75	D	T34D157(1)125(2)(3)(4)S	1.6	5	50	2750	1000	
240	75	D	T34D247(1)125(2)(3)(4)S	1.0	10	50	2500	1000	
350	62	D	T34D357(1)125(2)(3)(4)S	0.8	25	250	3000	2000	


Notes

- Typical AC ripple current values at 85 °C, 40 kHz
- Part number definitions:
 - (1) Capacitance tolerance: K, M
 - (2) Termination and packaging: A = 100 % tin, bulk; B = std., tin / lead, bulk
 - (3) Reliability level: Z = non-ER
 - (4) Style number: 6 = high temperature film insulation, 8 = no film insulation



TYPICAL PERFORMANCE CHARACTERISTICS OF T34 CAPACITORS

ELECTRICAL CHARACTERISTICS	
ITEM	PERFORMANCE CHARACTERISTICS
Operating temperature range	-55 °C to +85 °C (to +200 °C with voltage derating)
Capacitor tolerance	± 20 %, ± 10 % at 120 Hz, at +25 °C
Capacitor change by temperature	Limit per Standard Ratings table
ESR	Limit per Standard Ratings table, at +25 °C, 120 Hz
DCL (leakage current)	Limit per Standard Ratings table
Reverse voltage	There shall be no continuous reverse voltage. Transient reverse voltage surges are acceptable under the following conditions: a) The peak reverse voltage is equal to or less than 1.5 V and the product of the peak current times the duration of the reverse transient is 0.05 As or less b) The repetition rate of the reverse voltage surges is less than 10 Hz
Surge voltage	The DC rated surge voltage is the maximum voltage to which the capacitors can be subjected under any conditions including transients and peak ripple at the highest line voltage. The DC surge voltage is 115 % of rated DC voltage.



PERFORMANCE CHARACTERISTICS	
ITEM	PERFORMANCE CHARACTERISTICS
Life testing	Capacitors shall be capable of withstanding life test at temperature +200 °C at derated voltage. After the test, the capacitors shall meet the following requirements: a) Capacitance shall be within +10 %, -20 % of the initial value b) ESR shall not exceed 200 % of the applicable value from “Standard Ratings” table

ENVIRONMENTAL CHARACTERISTICS		
ITEM	CONDITION	COMMENTS
Seal	MIL-STD-202, method 112, condition C	When the capacitors are tested as specified there will be no evidence of leakage.
Moisture resistance	MIL-STD-202, method 106	10 continuous cycles, 6 V _{DC}
Barometric pressure (reduced)	MIL-STD-202, method 105, condition E	Altitude 150 000 feet



MECHANICAL CHARACTERISTICS		
ITEM	CONDITION	COMMENTS
Shock (specified pulse)	MIL-STD-202, method 213	Test condition D (500 g)
Vibration, high frequency	MIL-STD-202, method 204	Test condition H (80 g)
Random vibration	MIL-STD-202, method 214	Test condition II-K (53.8 g)
Thermal shock	MIL-STD-202, method 107	Test condition A, 30 cycles
Solderability	MIL-STD-202, method 208	ANSI / J-STD-002, test A
Terminal strength	MIL-STD-202, method 211	Condition A
Resistance to solder heat	MIL-STD-202, method 210	Condition C
Terminals	MIL-STD-1276	Terminals shall be as specified in MIL-STD-1276. The length and diameter of the terminals shall be as specified in Dimensions table. All terminals shall be permanently secured internally and externally, as applicable. All external joints shall be welded.
Marking	MIL-STD-1285	Marking of capacitors conforms to method I of MIL-STD-1285 and include capacitance (in μF), capacitance tolerance letter, rated voltage, date code, lot symbol and Vishay trademark.

SELECTOR GUIDES	
Tantalum Selector Guide	www.vishay.com/doc?49054
Parameter Comparison Guide	www.vishay.com/doc?42088



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.