



TapeCase Ltd.  
1982 Lunt Ave, Elk Grove Village, IL 60007  
phone: (847) 299-7880  
fax: (847) 299-7804  
www.tapecase.com  
sales@tapecase.com

---

## Metalized Polyester Film Tape

### MPFT Series

#### Product Description

---

1.0 mil metalized polyester film with brilliant, vibrant mirror-like finish; coated with an aggressive long lasting acrylic adhesive system. Tapes have excellent chemical and thermal stability. Silver can be qualified to meet Federal Specification #L-T-100B, Type II.

#### Applications

---

Reflective Shielding; industrial & graphic arts; decorative trim, automotive trim, nameplates, electric appliances, advertising displays; suitable for micro film splicing; also can be used in photo sensing applications to detect splices and to facilitate roll changeovers.

#### Typical Physical Properties

---

Thickness	2 mil
Adhesive	Acrylic
Tensile	24 lbs/in.
Adhesion	45 oz/in.
Elongation	100%
Temperature	-60° - 300° F

#### Available Colors

---

Black, Gold, Red, Green, Blue, Silver



**TapeCase Ltd.**  
**1982 Lunt Ave, Elk Grove Village, IL 60007**  
**phone: (847) 299-7880**  
**fax: (847) 299-7804**  
**www.tapecase.com**  
**sales@tapecase.com**

## **Available Sizes**

---

<b>Width</b>	<b>Length</b>
1/4"	72YDS or 5YDS
3/8"	72YDS or 5YDS
1/2"	72YDS or 5YDS
3/4"	72YDS or 5YDS
1"	72YDS or 5YDS
1.5"	72YDS or 5YDS
2"	72YDS or 5YDS
3"	72YDS or 5YDS
4"	72YDS or 5YDS
6"	72YDS or 5YDS

**Available Core Sizes: 1.5" for 5 yd rolls and 3" for 72yd rolls**

**NOTE:**

- 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers..*
- 2. The above values are "Typical Values" which have a nominal range about them and are not intended for specification purposes.*