



Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 78.4 mm, Colour: Blue

RAL: Ähnlich 5005

Business data

Article number	<u>27160.5</u>
Article name	PQI 6/10 BU
GTIN (EAN)	4044211234355
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	16.82 g
Weight per piece (including packaging)	17.23 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	27160.9
Product description	Insulated cross-connector

Technical data

Dimensions

Length	4 mm
Width	78.4 mm
Height	22.5 mm
Pitch size	8.1 mm

Ratings

Max. voltage	800 V
Rated current	41 A
Current load, max.	41 A
Rated cross-section	6 mm ²
Contamination degree	3

Connection data

No. of poles	10
--------------	----

Materials

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C

Further technical data

Mounting type	Plug in
Insulation available	✓
Touch protection is available	✓
Number of bridged terminals	10

Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2023-06-14
REACH Candidate Substance Note	No
RoHS Conform	yes

Media

Accessories

##INVERSE##CONTA-CONNECT



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5,
Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
<u>27021.2</u>	PSL 6/3A GNYE	4044211223960	50 ST



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5,
Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
<u>27023.2</u>	PSL 6/4A GNYE	4044211224004	50 ST



Protective earth terminal, Push-in connection, Mounting type: Mounting rail TS 35/7.5,
Rated cross-section: 6 mm², Width: 8.1 mm, Colour: Green-yellow

Article number	Article name	GTIN (EAN)	Packaging unit
<u>27019.2</u>	PSL 6/2A GNYE	4044211223922	50 ST