Data sheet

3443.8 AQI 10/8/18 YE





External insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 80.9 mm, Rated current:

57 A; Colour: Yellow

RAL: 1026

Business data

Article number	<u>3443.8</u>
Article name	AQI 10/8/18 YE
GTIN (EAN)	4044211137588
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	13.8 g
Weight per piece (including packaging)	14 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Product description	External insulated cross-connector
Colour	Yellow

Data sheet





Technical data		
Dimensions		
Width	80.9 mm	
Pitch size	8 mm	
Ratings		
Rated current	57 A	
Contamination degree	3	
Connection data		
No. of poles	10	
Materials		
Material	Copper	
Surface	Tin-plated	
Insulation housing	Polyamide 6.6	
Flammability class UL 94	V-2	
Working temperature, min.	-40 °C	
Working temperature, max.	105 °C	
Further technical data		
Mounting type	Plug in	
Insulation available	✓	
Touch protection is available	✓	
Number of bridged terminals	10	
Environmental Product Compliance		
REACH Conform	yes	
REACH Reference date	2023-06-14	
REACH Candidate Substance Note	No	
RoHS Conform	yes	

Data sheet 3443.8 AQI 10/8/18 YE



Media

Data sheet

3443.8 AQI 10/8/18 YE



Accessories

##INVERSE##CONTA-CONNECT



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1104.2	SIK 10/LED(RD)/20-30V DC/40-60V AC BG	4044211016753	25 ST



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1103.2	SIK 10/LED(RD)/12V DC/24V AC BG	4044211016548	25 ST



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1105.2	SIK 10/LED(RD)/40-60V DC/80-120V AC BG	4044211016906	25 ST



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1107.2	SIK 10/2 LED's(RD)/24V DC BG	4044211016920	25 ST



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1106.2	SIK 10/LED(RD)/115V DC/230V AC BG	4044211016913	25



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17042.2	SIK 10/ST BG	4044211155797	25

Data sheet 3443.8 AQI 10/8/18 YE



##INVERSE##CONTA-CONNECT



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1101.2	SIK 10 BG	4044211016388	50



Fused terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Black

Article number	Article name	GTIN (EAN)	Packaging unit
<u>17364.4</u>	SIK 10 PA-G BK	4044211178406	50 ST



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 8 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
17044.2	SIK 10/ST/5x20 BG	4044211155827	25 ST