

# Data sheet

## 3744.2 ZVQI 2,5 OG



Vertical insulated cross-connector, No. of poles: 1, Colour: Orange

### Business data

Article number	3744.2
Article name	ZVQI 2,5 OG
GTIN (EAN)	4044211060534
Packaging unit	20
Quantity unit	PC
Weight per piece (not including packaging)	1.1 g
Weight per piece (including packaging)	1.16 g
Unit of weight	G
Customs number	85389099
Country of origin	BG
Product description	Vertical insulated cross-connector
Colour	Orange

### Technical data

#### Dimensions

Length	4.3 mm
--------	--------

Width	5.2 mm
-------	--------

#### Ratings

Voltage with partition, max.	800 V
------------------------------	-------

Voltage without partition, max.	800 V
---------------------------------	-------

Rated current	24 A
---------------	------

Rated cross-section	2.5 mm <sup>2</sup>
---------------------	---------------------

Contamination degree	3
----------------------	---

#### Connection data

No. of poles	1
--------------	---

#### Materials

Material	Bronze
----------	--------

Surface	Tin-lead
---------	----------

Insulation housing	Polyamide 6.6
--------------------	---------------

Flammability class UL 94	V-2
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	105 °C
---------------------------	--------

#### Further technical data

Mounting type	Plug in
---------------	---------

Insulation available	✓
----------------------	---

Touch protection is available	✓
-------------------------------	---

Number of bridged terminals	1
-----------------------------	---

#### Environmental Product Compliance

REACH Conform	yes
---------------	-----

REACH Reference date	2023-06-14
----------------------	------------

REACH Candidate Substance Note	No
--------------------------------	----

RoHS Conform	yes
--------------	-----


---

### Media

---


### Accessories

#### ##INVERSE##CONTA-CONNECT




Three-level initiator terminal | Multi-wire terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm<sup>2</sup>, Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3590.2</u>	ZIKD 2,5 BG	4044211059460	50



Three-level initiator terminal | Multi-wire terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm<sup>2</sup>, Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3592.2</u>	ZIKD 2,5/PE/L/L BG	4044211059507	50



Three-level initiator terminal | Multi-wire terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm<sup>2</sup>, Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>17037.2</u>	ZIKD 2,5/L-L-N BG	4044211155742	50 ST



Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm<sup>2</sup>, Width: 5.1 mm, Colour: Beige


Article number	Article name	GTIN (EAN)	Packaging unit
<u>3575.2</u>	ZRKD 2,5/ZBA BG	4044211059194	100



Double-level terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm<sup>2</sup>, Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>3562.2</u>	ZRKD 2,5 BG	4044211151836	100

#### ##INVERSE##CONTA-CONNECT



Three-level initiator terminal | Multi-wire terminal, Tension-spring connection, Mounting type: Mounting rail TS 35/7.5, Rated cross-section: 2.5 mm<sup>2</sup>, Width: 5.1 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
<u>17037.2</u>	ZIKD 2,5/L-L-N BG	4044211155742	50 ST