

https://www.phoenixcontact.com/us/products/3260161



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Insertion bridge, pitch: 25 mm, number of positions: 4, length: 73 mm, color: red



Commercial data

Item number	3260161
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE29
Product key	BE2Z2X
Catalog page	Page 138 (C-1-2019)
GTIN	4055626137476
Weight per piece (including packing)	109.58 g
Weight per piece (excluding packing)	109.58 g
Customs tariff number	85366990
Country of origin	PL



https://www.phoenixcontact.com/us/products/3260161



Technical data

Product properties

Product type	Insertion bridge
Number of positions	4
Pitch	25 mm

Electrical properties

Maximum load current	150 A

Connection data

Maximum load current	150 Δ
Maximum load current	130 A

Dimensions

Width	97.8 mm
Height	73.3 mm
Depth	28.6 mm
Length	73.3 mm
Pitch	25 mm

Material specifications

Color	red
Material	Metal
Flammability rating according to UL 94	V0
Coating	tin-plated
Insulating material	PA

Mounting

|--|



https://www.phoenixcontact.com/us/products/3260161



Classifications

ECLASS

	ECLASS-11.0	27141140
	ECLASS-12.0	27141140
	ECLASS-13.0	27250303
ET	TIM .	
	ETIM 9.0	EC000489

UNSPSC

UNSPSC 21.0	39121400
-------------	----------



https://www.phoenixcontact.com/us/products/3260161



Environmental product compliance

EU RoHS

20 1.01.0	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com