

# WS PT 10 - Warning label



1029030  
<https://www.phoenixcontact.com/us/products/1029030>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Warning label, yellow/black, labeled: Lightning flash, mounting type: plug in, for terminal block width: 10.2 mm

## Your advantages

- Mains terminal blocks are reliably covered and marked using warning labels

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1029030             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales key                            | BE22                |
| Product key                          | BE224Z              |
| Catalog page                         | Page 420 (C-1-2019) |
| GTIN                                 | 4055626529738       |
| Weight per piece (including packing) | 1.86 g              |
| Weight per piece (excluding packing) | 1.34 g              |
| Customs tariff number                | 49119900            |
| Country of origin                    | IN                  |

# WS PT 10 - Warning label

1029030

<https://www.phoenixcontact.com/us/products/1029030>



## Technical data

### Product properties

|                     |                       |
|---------------------|-----------------------|
| Product type        | Warning label printed |
| Type                | Rectangle             |
| Number of positions | 5                     |
| Pitch               | 10.2 mm               |

### Marking

|          |                 |
|----------|-----------------|
| Printing | Lightning flash |
|----------|-----------------|

### Dimensions

|        |         |
|--------|---------|
| Width  | 9.3 mm  |
| Height | 9.7 mm  |
| Depth  | 9.7 mm  |
| Pitch  | 10.2 mm |

### Material specifications

|                                        |                                |
|----------------------------------------|--------------------------------|
| Color                                  | yellow/black                   |
| Material                               | PA                             |
| Flammability rating according to UL 94 | V0                             |
| Components                             | free from silicone and halogen |

### Environmental and real-life conditions

#### Ambient conditions

|                                          |                                                                           |
|------------------------------------------|---------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)       |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                           |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                             |

### Standards and regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

### Mounting

|               |         |
|---------------|---------|
| Mounting type | plug in |
|---------------|---------|

# WS PT 10 - Warning label

1029030

<https://www.phoenixcontact.com/us/products/1029030>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 40200103 |
| ECLASS-12.0 | 40200103 |
| ECLASS-13.0 | 40200507 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001777 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 55121700 |
|-------------|----------|

# WS PT 10 - Warning label

1029030  
<https://www.phoenixcontact.com/us/products/1029030>



## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)