

https://www.phoenixcontact.com/us/products/3241240



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Ferrule, color: silver



### Commercial data

Item number	3241240
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BH34
Product key	BH3412
Catalog page	Page 480 (C-3-2019)
GTIN	4046356908139
Weight per piece (including packing)	3.63 g
Weight per piece (excluding packing)	3.63 g
Customs tariff number	85369010
Country of origin	DE



https://www.phoenixcontact.com/us/products/3241240



### Technical data

### Notes

General	These ferrules are not included in DIN 46228-1: 1992-08
Product properties	
Product type	Cable end sleeve

stranded conductors, class 2, 5, 6 / B, C, K, M

### Connection data

#### Conductor connection

Conductor category

Conductor cross section flexible max.	50 mm²
Conductor cross section AWG max.	1/0
Stripping length	40 mm

### **Dimensions**

Dimensional drawing	
Maximum stripping length	40 mm
Ferrule diameter	10.3 mm
Sleeve wall thickness	0.3 mm
Inner dimensions of the insulating collar	13 mm

### Material specifications

Color	silver
Material	CU-DHP
Coating	tin-plated (galvanic)

### Environmental and real-life conditions

#### Ambient conditions

Tanalan dan dan dan dan dan dan dan dan dan d		
	Permanent temperature	105 °C
	Short-term temperature	120 °C


3241240

https://www.phoenixcontact.com/us/products/3241240



### Drawings

### Dimensional drawing



Sleeve length (b), insulating collar inner dimension (d), sleeve diameter (k), sleeve wall thickness (j)



https://www.phoenixcontact.com/us/products/3241240



### Classifications

### **ECLASS**

ECLASS-11.0	27400201
ECLASS-12.0	27400201
ECLASS-13.0	27400201
ETIM	
ETIM 9.0	EC000005
UNSPSC	

## U



https://www.phoenixcontact.com/us/products/3241240



# Environmental product compliance

EU RoHS	
---------	--

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

3241240

https://www.phoenixcontact.com/us/products/3241240



#### Accessories

### CRIMPFOX 50R - Crimping pliers

1212041

https://www.phoenixcontact.com/us/products/1212041



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 35 mm<sup>2</sup> ... 50 mm<sup>2</sup>, lateral entry, WM crimp

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com