

**H1,0/16D R BD GSP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Similar to illustration**

- Linked wire-end ferrules on reel (5,000 pcs.)
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |                                               |
|------------|-----------------------------------------------|
| Version    | Wire-end ferrule, Standard, 12 mm, 10 mm, red |
| Order No.  | <a href="#">1476090000</a>                    |
| Type       | H1,0/16D R BD GSP                             |
| GTIN (EAN) | 4050118282924                                 |
| Qty.       | 5,000 pc(s).                                  |
| Packaging  | Reel                                          |

## H1,0/16D R BD GSP

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |         |
|------------|---------|
| Net weight | 0.138 g |
|------------|---------|

## Technical data

| Description of article | Wire-end ferrules on reel, red | Version | Standard |
|------------------------|--------------------------------|---------|----------|
|------------------------|--------------------------------|---------|----------|

## Wire-end ferrules

|                             |                   |                                         |         |
|-----------------------------|-------------------|-----------------------------------------|---------|
| Collar diameter (D2)        | 3 mm              | Colour code                             | DIN     |
| Conductor cross-section     | 1 mm <sup>2</sup> | Contact surface diameter (D1)           | 1.4 mm  |
| Contact surface length (L2) | 10 mm             | L1 in mm                                | 16 mm   |
| Metal sleeve thickness (S1) | 0.15 mm           | Plastic collar thickness (S2)           | 0.25 mm |
| Stripping length            | 12 mm             | Wire connection cross section AWG, max. | AWG 17  |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ETIM 9.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |
| ECLASS 12.0 | 27-40-02-01 | ECLASS 13.0 | 27-40-02-01 |

## Approvals

Approvals



|                       |            |
|-----------------------|------------|
| ROHS                  | Conform    |
| UL File Number Search | UL Website |
| Certificate No. (UR)  | E354986    |

## Downloads

|                    |                                                                                          |
|--------------------|------------------------------------------------------------------------------------------|
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>                                                 |

**H1,0/16D R BD GSP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Drawings****Drawing**