SPECIFICATIONS

SPECIFICATIONS	
ACCURACY	Setting: ±0.1% of set time of ±50mSec Repeat: ±0.1%
RESET	Reset time < 100 msec, Front Key, Interruption of Power
OUTPUT CONTACT	SPDT (1 C/O)
CONTACT RATIN	G 8A @ 250V AC
MODES	On delay (A) Interval (B) Asymmetrical cyclic OFF first (C) Asymmetrical cyclic ON first (D) Cyclic equal OFF first (E) Cyclic equal ON first (F) Pulse output (H) Delay on break (I) Delay on make/break (K) Interval after break (L) Single shot (P) Retriggerable Single shot (Q) Latching relay (R) Delay with Totalise (t) Interval with Totalise (U)
TIME RANGES	0 - 99.9 sec/min/hr 0 - 999 sec/min/hr 0 - 9:59 min:sec 0 - 9:59 hr:min
SUPPLY VOLTAGE	20-240V AC/DC AC : (50 / 60 Hz)
POWER CONSUMPTION	4 VA max
TEMPERATURE	Operating: 0 to 50°C (32 to 122°F) Storage: -20 to 75°C (-4 to 167°F)
HUMIDITY (NON-CONDENS	95% RH ING)
WEIGHT	0.163 lbs.
PROTECTION LEVEL	IP40 for Casing IP20 for Terminals



 PART NO.
 SUPPLY VOLTAGE

 175MD
 20-240V AC/DC


 AC: 50/60Hz




Multi-Function Timer "With Display"

- 15 Functions
- 8 Time Ranges
- Front Key Pad Setting
- Universal supply voltage
- Slim, Space Saving Design
- DIN Rail Mount

DIMENSIONS (MILLIMETERS)



TERMINAL CONNECTIONS



TIMING DIAGRAMS

