



Relays & Contactors > Relays > Time Delay Relays



Type of Control: **Knob**
Input Voltage: **120 – 110 VAC**
Contact Current Rating (Max): **10 A**
Mode of Operation: **On-Delay**
Delay Time: **5 – 50 seconds**

Features

Product Type Features

Relay Connection Type	Terminals
Terminal Configuration	Screw Terminals

Electrical Characteristics

Actuating System	AC
Input Voltage	120 – 110 VAC

Contact Features

Contact Arrangement	2 Form C, DPDT, 2 C/O
Type of Control	Knob
Contact Current Rating (Max)	10 A
Delay Time	5 – 50 seconds

Mechanical Attachment

Product Mounting Feature Type	Mounting Brackets
Product Mount Type	Chassis

Dimensions

Product Width	82.55 mm[3.25 in]
Product Length	114.8 mm[4.52 in]
Product Height	78.4 mm[3.09 in]



Usage Conditions

Operating Temperature Range	-30 – 75 °C
-----------------------------	-------------

Operation/Application

Mode of Operation	On-Delay
-------------------	----------

Other

Repeatability (Max)	±5%
---------------------	-----

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE’s information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) ‘Guidance on requirements for substances in articles’(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of ‘complex object’, the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA “Guidance on requirements for substances in articles” (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts





TE Part # 2-1423159-6


7012PD=RLY,STD,ON,2P,125VDC,50

Customers Also Bought



TE Part #207359-1

RECEPT HSG,3 POSN,METRIC



TE Part #1-640507-0

02P MR II CAP HSG



TE Part #207304-1

24 POS SQ GRID METRIMATE-PLUG




TE Part #350538-1

UMNL PIN 20-14 .0126 PTPBR



TE Part #1393143-5

27E121=SOCKET,KUP,11,SCW,PLE



TE Part #640545-2

MR SPLIT PIN 26-18 AUPHBRZ LP



TE Part #2-321233-1

TERMINAL,PIDG SPD 16-14 8



TE Part #207360-1

PLUG HSG,3 POSN,METRIC



TE Part #350705-1

UMNL SPLIT PIN 20-14 PTPBR L/P



TE Part #4-1393159-6

20C314=SPRING,HOLD,DOWN,KUP