

Agastat

TE Internal #: 1-1423157-5

Time Delay Relays, Knob, 120 – 110VAC Input Voltage, 10A Contact Current Rating (Max), On-Delay, 1 – 10 minutes Delay Time, Chassis

View on TE.com >



Relays & Contactors > Relays > Time Delay Relays



Type of Control: **Knob**

Input Voltage: 120 – 110 VAC

Contact Current Rating (Max): 10 A Mode of Operation: On-Delay Delay Time: 1 – 10 minutes

Features

Product Type Features

Relay Connection Type	Terminals
Terminal Configuration	Screw Terminals
Electrical Characteristics	
Actuating System	AC
Input Voltage	120 – 110 VAC

Contact Features

Contact Arrangement	2 Form C, DPDT, 2 C/O
Type of Control	Knob
Contact Current Rating (Max)	10 A
Delay Time	1 – 10 minutes

Mechanical Attachment

Pro	oduct Mounting Feature Type	Mounting Brackets
Pro	oduct Mount Type	Chassis
Dim	aensions	

Dimensions

Product Width	82.55 mm[3.25 in]
Product Length	114.8 mm[4.52 in]
Product Height	78.4 mm[3.09 in]



Usage Conditions

Operating Temperature Range	-30 – 75 °C	
Operation/Application		
Mode of Operation	On-Delay	
Other		
Repeatability (Max)	±10%	

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts





Customers Also Bought

















TE Part #A30155-000 MCK-5-1V

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1423157-5_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1423157-5_L.3d_igs.zip

English

Time Delay Relays, Knob, 120 – 110VAC Input Voltage, 10A Contact Current Rating (Max), On-Delay, 1 – 10 minutes Delay Time, Chassis



Customer View Model
ENG_CVM_CVM_1-1423157-5_L.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.