



Relays & Contactors > Relays > Time Delay Relays



Type of Control: **Knob**
Input Voltage: **120 – 110 VAC**
Contact Current Rating: **10 A**
Mode of Operation: **On-Delay**
Delay Time: **3 – 30 minutes**

Features

Electrical Characteristics

Actuating System	AC
Input Voltage	120 – 110 VAC

Contact Features

Contact Arrangement	2 Form C, DPDT, 2 C/O
Type of Control	Knob
Contact Current Rating	10 A
Delay Time	3 – 30 minutes

Termination Features

Relay Connection Type	Terminals
Terminal Configuration	Screw Terminals

Mechanical Attachment

Product Mounting Feature Type	Mounting Brackets
Product Mount Type	Chassis

Dimensions

Product Width	82.55 mm[3.25 in]
Product Length	114.8 mm[4.52 in]
Product Height	78.4 mm[3.09 in]



Usage Conditions

Operating Temperature Range	-30 – 75 °C
-----------------------------	-------------

Operation/Application

Mode of Operation	On-Delay
-------------------	----------

Other

Repeatability (Max)	±10%
---------------------	------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Cadmium oxide (10% in Contact) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2-1423159-3

7012PC=RLY,STD,ON,2P,125VDC,15

Customers Also Bought

TE Part #321165

TERMINAL,SOLIS R 16-14HD 1/2

TE Part #1393143-7

27E123=SOCKET,KRP,11,SCW,PLE

TE Part #2-1419106-3

27E891=SOCKET,KRPA,8,OCTAL,POL

TE Part #6-1393104-5

KRPA-14AG-120=KRPA

TE Part #31943

KNIFE DISCONNECT,DG 16-14

TE Part #4-2027183-3

KUEP-11D15-125=RELAY,3A,2C, AGCDO,QC.187,

TE Part #1423162-2

7022AB=RLY,STD,OFF,2P,120VAC,5

TE Part #305183-8

ET TYPE IV #20

TE Part #1-1445022-1

MICRO MNL RFECEPT HSG SINGLE R

TE Part #1520204-1

8690K2=10 AMP TOGGLE DPDT

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1423157-0_L.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2-1423157-0_L.3d_igs.zip

English



Customer View Model

[ENG_CVM_CVM_2-1423157-0_L.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[5-1773450-5_sec12_7000](#)

English