Product data sheet Characteristics

SM522B114FS

Hyde Park, superprox ultrasonic dual level sensor

Main	
Range of Product	Hyde Park
Sensor Type	Ultrasonic sensor
Series name	Standard format
Device short name	SM522
Sensor design	Compact
Material	Plastic
[Us] rated supply voltage	100240 V AC
Electrical connection	Cable
Product Specific Application	Other terminal unit
[Sd] sensing range	0.173.28 ft (0.0511 m)
IP degree of protection	IP66

Complementary

[Sn] nominal sensing distance	3.28 ft (1 m)
Type of sensing window	Fixed
Transmission frequency	200 kHz

Ordering and shipping details

Category	US10DS222490
Discount Schedule	0DS2
GTIN	03389119093859
Returnability	No

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Not applicable, out of EU RoHS legal scope	

Contractual warranty

Contraction Warranty	
Warranty	18 months