# Product data sheet Characteristics

# SC600AB00

# Hyde Park, superprox ultrasonic proximity sensor, sc

#### Main

Hyde Park
Ultrasonic sensor
Superprox +
SC600
Flat form
Configurable
Plastic
ULTEM
Silicone rubber
Discrete
4-wire
1224 V DC overload and short-circuit protection
1028 V DC
Cable, 9.84 ft (3 m)
Discrete proximity

#### Complementary

[Sn] nominal sensing distance	10.00 in (254 mm)
Maximum differential travel	0.01 in (0.35 mm)
Blind zone	2.01 in (51 mm)
Transmission frequency	500 kHz
Repeat accuracy	0.07 %
Beam angle	7 °
Minimum size of detected object	Cylinder diameter 1.59 mm - up to 76.2 mm sensing distance
Current Consumption	50 mA
Maximum switching current	100 mA reverse polarity protection
Height	0.64 in (16.25 mm)
Width	1.2 in (30 mm)
Depth	0.64 in (16.25 mm)
Length	2.91 in (73.91 mm)
Net Weight	0.15 lb(US) (0.07 kg)

#### Environment

Product Certifications	UL	
Marking	CE	
NEMA degree of protection	NEMA 4X indoor use only)	
IP degree of protection	IP67	
Ambient Air Temperature for Operation	32140 °F (060 °C)	
Ambient Air Temperature for Storage	-40212 °F (-40100 °C)	
Relative humidity	100 % without condensation	
Vibration resistance	+/-1 mm 1055 Hz)IEC 60068-2-6	
Shock resistance	30 gn in all 3 axes 11 ms IEC 60068-2-27	
Resistance to electromagnetic fields	9.1 V/m (10 V/m) level 3 IEC 61000-4-3	
Resistance to fast transients	1 kV level 3 IEC 61000-4-4	

## Ordering and shipping details

Category	US10DS222490
Discount Schedule	0DS2
GTIN	3389119086318
Returnability	No

## Packing Units

PCE	
1	
5.63 in (14.288 cm)	
2.50 in (6.35 cm)	
5.63 in (14.288 cm)	
1.92 oz (54.431 g)	
	1 5.63 in (14.288 cm) 2.50 in (6.35 cm) 5.63 in (14.288 cm)

### Offer Sustainability

REACh Regulation  EU RoHS Directive  Not applicable, out of EU RoHS legal scope	hemicals including: Diisononyl of California to cause cancer, own to the State of California arm. For more information go to
ELL DoUS Directive	
EU RoHS Directive Not applicable, out of EU RoHS legal scope	

#### Contractual warranty

V	/arranty	18 months	