

Model Numbering Guide – OCXO

Available options

Type	Package (mm)	Supply Voltage (V)	Pulling Range (ppm)	Freq. Stability (ppb)	Temp. Range(°C)	Output Logic and Symmetry	Oscillator Mode	Pin out	Lead Free	Dash	Freq. (MHz)
N: OCXO	N: 9.7x7.5 K: 14x9.6 (SMD) F: 20.3x12.7 P: 20.6x20.6 J: 25.4x22.1 (SMD) A: 25.4x25.4 I: 36.3x27.2	E: 3.3 T: 5 A: 12	K: ±0.2 H: ±0.4 C: ±0.5 D: ±1 G: ±3 E: ±5 N: No Voltage Control Function	R: ±2 A: ±5 B: ±10 C: ±20 E: ±30 G: ±50	B: 0~+50 E: 0~+70 C: -20~+70 D: -30~+70 L: -40~+85	W: Sine wave J: CMOS15pF / 50±5% S: Clipped Sine Wave	N: IT Fundamental H: SC 3rd overtone	N : Normal (Please refer to "outline drawing") Y: Channel ID	F: RoHs Compliant Y: Channel	–	XX.XXXXXX

N	A	T	H	C	E	W	H	N	F	–	10.000000
----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	----------	------------------

*Not all combinations of options are available.

Example: NATHCEWHNF-10.000000

Type	OCXO
Package	25.4 x 25.4 mm
Supply Voltage(V)	5 V
Pulling Range	±0.4 ppm
Freq. Stability	±20 ppb
Temp Range	0~+70 °C
Output	Sine wave
Pin Out	Normal
Lead Free	RoHs Compliant
Frequency	10.000000 MHz