



# BP36V60ART2U | EXTENDED BATTERY MODULE



## Extend battery runtime for UPS systems during power outages.

The CyberPower BP36V60ART2U rack/tower convertible Extended Battery Module (EBM), which extends battery runtimes during power outages, is designed for Smart App Online UPS systems OL1000RTXL2U, OL1000RTXL2UN, OL1500RTXL2U and OL1500RTXL2UN. This EBM takes 2U of rack space and can be installed in a rack or tower configuration to match the UPS form factor. It also has a built-in battery charger, providing Fast Charge Technology to quickly restore the backup power supply to full capacity.

Up to ten EBMs can be added to the UPS, and the module's DC plug-and-play power connectors allow for daisy-chaining additional EBMs to a UPS system. The BP36V60ART2U typically has a UPS charging time of four hours, regardless of whether one or ten EBMS are installed, and comes with a three-year warranty.

### ELIGIBLE MODELS

- OL1000RTXL2U
- OL1000RTXL2UN
- OL1500RTXL2U
- OL1500RTXL2UN

### TYPICAL APPLICATIONS

- Corporate and Enterprise Servers
- Network and Storage Devices
- Edge Closets
- PBX and VoIP Installations

### FEATURES

- Output: 36V/60A
- Typical Recharge Time: 4 hours (0-90%)
- Battery Type & Quantity: 12V/9AH (6)
- Form Factor: Rack/Tower
- Hot Swappable: Yes
- Fast Charge Technology: Yes

## SPECIFICATIONS

GENERAL	
Amperage	60A
DC Voltage	36 VDC
BATTERY	
Built-in Charger	Yes
Battery Type	Sealed Lead-Acid Battery
Battery Quantity	6

BATTERY - CONT.	
Replacement Battery Cartridge	(1) RB1290X3R & (1) RB1290X3L
Typical Recharge Time	4 Hours (0-90%)
Expansion Ready (Daisy-Chain)	Yes
Battery Size	12 V / 9 Ah
Hot Swappable	Yes
User Replaceable Battery	Yes

# BP36V60ART2U | EXTENDED BATTERY MODULE



## SPECIFICATIONS - CONT.

PHYSICAL	
Rack Size	2U
Mounting Hardware	Included
Enclosure Construction	Steel
Dimensions (Width/Height/Depth) cm	43.18 x 8.89 x 42.93 (cm)
Dimensions (Width/Height/Depth) (in)	17 x 3.5 x 16.9 (in)
Dimensions (Width/Height/Depth) (mm)	432 x 89 x 429 (mm)
Weight (kg)	22.95
Weight (lb)	50.6
Shipping Dimensions (Width/Height/Depth) (in)	21.5 x 9.75 x 22.5 (in)
Shipping Dimensions (Width/Height/Depth) (mm)	546.1 x 247.65 x 571.5 (mm)
Shipping Weight (kg)	29.71
Shipping Weight (lb)	65.5

ENVIRONMENTAL	
Storage Elevation	0 - 50000 ft (0 - 15239 m)
Operating Temperature	32 - 104 °F (0 - 40 °C)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
Operating Elevation	0 - 10000 ft (0 - 3048 m)
Storage Relative Humidity	0 - 95% (non-condensing)
Operating Relative Humidity	0 - 90 % (non-condensing)
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1778 CSA C22.2 NO.107.3 FCC Part 15 Class B
WARRANTY	
Product Warranty	3 Year Limited Warranty
Extended 2-Year Warranty	WEXT5YR-BP1