

# CyberPower

## PR1500RTXL2UTAA SMART APP SINEWAVE UPS



Protect corporate and network servers, telecom installations, and VoIP systems.

The PR1500RTXL2UTAA is a New Smart App Sinewave rack/tower convertible UPS with line-interactive topology, surge protection, and battery backup. CyberPower's New Smart App Sinewave series has sine wave output to eliminate power gaps that can be detected by sensitive equipment and cause unexpected shutdowns.

The New Smart App Sinewave PR1500RTXL2UTAA improves battery life through battery equalization technology and Automatic Voltage Regulation (AVR), which corrects minor power fluctuations without switching to battery power. The new chassis design with an easy-to-access toolless front panel, color-coded rear panel, and captive screws for battery panel access make installations and battery changes simple and fast. The PR1500RTXL2UTAA also has a new LCD panel that rotates 90°, tilts for a better viewing angle, and provides information on 47 different settings including UPS stats, UPS setup and control management, and testing options.

### TYPICAL APPLICATIONS

- Servers
- Workstations
- Network Devices
- Telecom Equipment

### FEATURES

- 1500 VA/1500 W
- Line-Interactive Topology
- GreenPower UPS™
- 2U Rack Mount/Tower Convertible

## SPECIFICATIONS

### GENERAL

UPS Topology	Line-Interactive
Energy Saving	GreenPower UPS™ Bypass Technology
ENERGY STAR® Qualified	Yes
Active PFC Compatible	Yes

### INPUT

Voltage	100 - 125 Vac
Frequency	47 - 63 Hz
Input Voltage Range	75 - 149 VAC
Plug Type	NEMA 5-15P
Plug Style	Right Angle, 45° Offset Right
Cord Length	10 ft.

### OUTPUT

VA	1500
Watts	1500
Automatic Voltage Regulation	Double boost, single buck
On Battery Voltage	100/110/120/125 Vac ± 5%
On Battery Frequency	50/60 Hz +/- 1%
On Battery Waveform	Sine Wave
Outlets - Total	8
Outlet Type	NEMA 5-15R
Outlets - Critical Load	4
Outlets - Battery & Surge Protected	8

# PR1500RTL2UTAA SMART APP SINEWAVE UPS



## SPECIFICATIONS CONT.

### OUTPUT CONT.

Rated Power Factor	1
Overload Protection	Internal Circuitry Limiting/ Circuit Breaker
Transfer Time	4ms typical

### BATTERY

Extended Battery Module	BP48VP2U02TAA
Runtime at Half Load (min)	17.9
Runtime at Full Load (min)	6.5
Battery Type	Sealed Lead-Acid
Battery Size	12V / 9AH
Hot-Swappable	Yes
Replacement Battery	RB1290X4J
Battery Quantity	4
User Replaceable	Yes
Typical Recharge Time	3 hrs
External Battery Pack Option	Yes

### SURGE PROTECTION & FILTERING

Network Protection RJ45	1-in, 1-out
Surge Suppression	2430
EMI/RFI Filtration	Yes

### MANAGEMENT & COMMUNICATION

Multifunction LCD Panel	47 Settings (27 setup and control items + 20 status updates and log menus)
HID Compliant USB Port	Yes
Serial Port	Yes
EPO Port	Yes
Contact Closure	Yes
Management Cable	USB Cable, EPO Cable

### MANAGEMENT & COMMUNICATION CONT.

LED Indicators	Power On, Line Mode, Battery Mode, Fault, Night Mode, Wiring Fault
Audible Alarms	Battery Mode, Low Battery, Overload, Overcharge, Overheat
Software	PowerPanel® Business
SNMP/HTTP Remote Monitoring	Yes - with optional RMCARD205TAA

### PHYSICAL

Rack Size	2U
Form Factor	Rack/Tower
Dimensions (WxHxD) (in.)	17.1 x 3.4 x 19.7
Weight (lbs.)	67.7
Shipping Dimensions (WxHxD) (in.)	22.1 x 10.8 x 24.4
Shipping Weight (lbs.)	81.1

### ENVIRONMENTAL

Operating Temperature	32°F to 104°F (0°C to 40°C)
Operating Relative Humidity	0 - 95% (non-condensing)
Storage Temperature	5°F to 113°F (-15°C to 45°C)
Maximum Operating Elevation	10,000 ft (3,000 m)
Maximum Storage Elevation	50,000 ft (15,000 m)
AC Mode Thermal Dissipation	71.7

### CERTIFICATIONS

Safety	UL1778, cUL107.1, FCC Class B
Environmental	RoHS Compliant

### WARRANTY

Product Warranty	Three-Years Limited
Connected Equipment Guarantee	Lifetime
CEG Amount	\$400,000