



# USB-C to USB-A Cable (M/M), USB 3.2 Gen 2 (10 Gbps), Thunderbolt 3 Compatible, 20-in. (50.8 cm)

#### MODEL NUMBER: U428-20N-G2











USB-C 3.2 to USB-A cable connects a smartphone or other USB-C device to the USB-A port on your computer, wall charger or car charger.

#### **Features**

USB Type-C to USB Type-A Cable Connects a USB-C Mobile Device to a Wall ChargerThis 20-inch USB-C 3.2 to USB-A cable allows you to connect any device with a USB-C or Thunderbolt 3 port, including MacBooks, Ultrabooks and Chromebooks, to a USB-enabled computer, charger, hard drive or other peripheral for the purpose of charging, powering, syncing or transferring data. Its 20-inch length makes it easy to carry in your briefcase or laptop bag for quick downloads and file transfers on the go.

Charges Devices and Transfers Data at Lightning-Fast USB 3.2 Gen 2 SpeedsThe USB-C to USB-A cable supports USB 3.2 Gen 2 data transfer rates up to 10 Gbps, which is double the speed of Gen 1. The Power Delivery cable also provides power output up to 3A (60 watts), which is more than sufficient for charging, syncing and powering compatible devices. The cable is backward compatible with previous USB generations, allowing you to use it with older equipment.

Reversible USB-C Connector Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

#### **Highlights**

- USB-C to USB-A cable is compatible with all USB-C and Thunderbolt 3 devices
- Supports USB 3.2 Gen 2 speeds up to 10 Gbps to ensure lightning-fast data transfers
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- Plug-and-play operation with no software required for easy, immediate installation

#### **Applications**

- Charge and sync a USB-C or Thunderbolt 3 mobile device from a USB-A wall charger or car charger up to 20 in. away
- Transfer data between an external hard drive or flash drive and your computer or laptop
- Connect your desktop computer to a docking station or hub with a USB-C or Thunderbolt 3 port

#### **System Requirements**

- Device with a USB-C or Thunderbolt 3 port
- Device with a USB-A port
- USB 3.2 Gen 2 compatibility required in both connected devices to achieve USB 3.2 Gen 2 speeds

### **Package Includes**

• U428-20N-G2 USB Type-C to USB Type-A Cable, M/M, 20 in.

## **Specifications**

| OVERVIEW             |                      |
|----------------------|----------------------|
| UPC Code             | 037332243423         |
| Technology           | Thunderbolt; USB 3.x |
| Cable Type           | Passive              |
| CONNECTIONS          |                      |
| CONNECTIONS          |                      |
| Side A - Connector 1 | USB A (MALE)         |





| Side B - Connector 1                   | USB C (MALE)                  |
|----------------------------------------|-------------------------------|
| Connector Plating                      | Nickel                        |
| Contact Plating                        | Gold                          |
| Connector Style                        | Straight                      |
| PHYSICAL                               |                               |
| Material of Construction               | PVC                           |
| Cable Jacket Color                     | Black                         |
| Cable Jacket Rating                    | VW-1                          |
| Cable Outer Diameter (OD)              | 4.5MM                         |
| Cable Length (ft.)                     | 1.7                           |
| Cable Length (m)                       | 0.52                          |
| Cable Length (in.)                     | 20                            |
| Cable Length (cm)                      | 50.8                          |
| Shipping Dimensions (hwd / in.)        | 9.00 x 7.00 x 0.50            |
| Shipping Dimensions (hwd / cm)         | 22.86 x 17.78 x 1.27          |
| Shipping Weight (lbs.)                 | 0.50                          |
| Shipping Weight (kg)                   | 0.23                          |
| Unit Dimensions (hwd / in.)            | 9.000 x 7.000 x 0.500         |
| Unit Packaging Type                    | Polybag                       |
| ENVIRONMENTAL                          |                               |
| Operating Temperature Range            | 32° to 113°F (0° to 45°C)     |
| Storage Temperature Range              | -40° to 158°F (-40° to 70°C)  |
| Operating Humidity Range               | 10% to 85%, Non-Condensing    |
| Storage Humidity Range                 | 5% to 90%, Non-Condensing     |
| FEATURES & SPECIFICATIONS              |                               |
| USB Specification                      | USB 3.2 Gen 2 (Up to 10 Gbps) |
| STANDARDS & COMPLIANCE                 |                               |
| Product Compliance                     | RoHS; REACH                   |
| WARRANTY & SUPPORT                     |                               |
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty     |





1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.