

1954643-1 ✓ ACTIVE



## Industrial USB IP67

TE Internal #: 1954643-1

USB Connectors, A, 2.0, Standard Profile, Receptacle, 1 Port, Cable Mount, Straight, Package, IP67, Wire-to-Wire, 4 Position, Industrial USB IP67

[View on TE.com >](#)

Connectors > Audio & Video Connectors > USB Connectors



USB Adapter Type: **A**

USB Version: **2.0**

Connector Profile: **Standard**

Connector & Housing Type: **Receptacle**

Number of Ports: **1**

### Features

#### Product Type Features

|                                   |                |
|-----------------------------------|----------------|
| USB Adapter Type                  | A              |
| USB Version                       | 2.0            |
| Connector & Housing Type          | Receptacle     |
| Connector System                  | Wire-to-Wire   |
| Sealable                          | Yes            |
| Connector & Contact Terminates To | Wire & Cable   |
| USB Connector Type                | USB 2.0 Type-A |

#### Configuration Features

|                     |   |
|---------------------|---|
| Number of Ports     | 1 |
| Number of Positions | 4 |

#### Body Features

|                        |                 |
|------------------------|-----------------|
| Shell Plating Material | Tin over Nickel |
| Connector Profile      | Standard        |

#### Contact Features



|  |                   |
|--|-------------------|
| Contact Mating Area Plating Material Thickness | .76 µm[29.92 µin] |
| Contact Mating Area Plating Material           | Gold              |
| Contact Current Rating (Max)                   | 1.5 A             |

### Mechanical Attachment

|                          |                            |
|--------------------------|----------------------------|
| Locking Feature          | With                       |
| PCB Mount Location       | Cable Mount                |
| PCB Mount Retention Type | None                       |
| Connector Mounting Type  | Cable Mount (Free-Hanging) |

### Housing Features

|                  |              |
|------------------|--------------|
| Housing Material | Polyester GF |
| Housing Color    | Black        |
| Body Orientation | Straight     |

### Usage Conditions

|                             |                           |
|-----------------------------|---------------------------|
| Soldering Temperature (Max) | 350 °C[662 °F]            |
| Operating Temperature Range | -55 - 85 °C[-67 - 185 °F] |

### Operation/Application

|                          |                                 |
|--------------------------|---------------------------------|
| Assembly Process Feature | None                            |
| Circuit Application      | Power, Signal & High Speed Data |

### Industry Standards

|                   |         |
|-------------------|---------|
| Industry Standard | USB 2.0 |
| IP Rating         | IP67    |

### Packaging Features

|                    |         |
|--------------------|---------|
| Packaging Quantity | 1       |
| Packaging Method   | Package |

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

|   |   |
|---|---|
| EU RoHS Directive 2011/65/EU                  | Compliant                                   |
| EU ELV Directive 2000/53/EC                   | Compliant                                   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold     |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2024 (240) |



Candidate List Declared Against: JAN 2021 (211)

Does not contain REACH SVHC

|                           |  |
|---------------------------|--|
| Halogen Content           | Not Yet Reviewed for halogen content         |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts



TE Part # 2355444-1  
RJ45 PROTECTION CAP



TE Part # 2355444-2  
RJ45 PROTECTION CAP (PBT)



TE Part # 1954637-1  
Plug Kit, USB Series A

### Also in the Series | Industrial USB IP67



USB Connectors(4)

### Customers Also Bought



## Documents

### Product Drawings

[Recpt Kit, Series A to Series A](#)

English

### CAD Files

[Customer View Model](#)

[ENG\\_CVM\\_CVM\\_1954643-1\\_A.2d\\_dxf.zip](#)

English

[3D PDF](#)

3D

[Customer View Model](#)

[ENG\\_CVM\\_CVM\\_1954643-1\\_A.3d\\_igs.zip](#)

English

[Customer View Model](#)

[ENG\\_CVM\\_CVM\\_1954643-1\\_A.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Datasheets & Catalog Pages

[1-1773463-4\\_INDUSTRIAL\\_USB\\_CONNECTORS](#)

English

[CONNECTIVITY SOLUTIONS FOR INFOTAINMENT APPLICATIONS](#)

English

### Product Specifications

[Application Specification](#)

English

1954643-1

USB Connectors, A, 2.0, Standard Profile, Receptacle, 1 Port, Cable Mount, Straight, Package, IP67, Wire-to-Wire, 4 Position, Industrial USB IP67



**Instruction Sheets**

**Instruction Sheet (U.S.)**

English