



- Multimedia
- Accesories
 - Datacom
 - Network

Order online @



or call 1.800.344.4539

DIGITUS® External premium HDD enclosure 2.5" USB 2.0 & Firewire A

- External aluminium case for 2.5" hard drives
- Conforms to USB 2.0 or USB2.0 and IEEE1394a specification (DA-70502-1)
- Data transfer rate up to 480 Mbps (USB) and 400 bps (Firewire A)
- Two Firewire ports, 1x 6-pin and 1x 4-pin (DA-70502-1)
- Conforms to ATA/ATAPI-6 specification (Rev.1.0 for USB)
- Conforms to USB storage class specification Ver.1.0
- Compatible with Win98/SE, 2000, ME and XP
- Supports Mac OS 9.0, supports LINUX 2.4.x and better
- LED power (green)/ status (red)
- Power supply via USB port, external power supply (optional)



DIGITUS® External S-ATA HDD enclosure 3.5" ALU

- Serial ATA 1.0 compliant
- Automation 3.0/1.5 Gbps transmission rate negotiation
- Support S-ATA Hot Plug
- · Support S-ATA connector
- Thinner and longer cable

192121 / DA-70585

- Serialize/ Deserialize a 40 Bit (double word aligned) or 10 Bit with 4X speed signal from/to the link layer
- Provide specified OOB signal detection and transmission
- 32 Bits CRC error checking on all data and control information
- Supports 32 Bits and 48 Bits LBA hard disk

DIGITUS External HDD enclosure 3.5" ALU S-ATA ⇒ S-ATA

Compatible with WIN98, WIN98 se, WIN 2000, WIN ME and WIN XP

DIGITUS® USB 1.1 to PS/2 adapter

Accessories

• Support MAC OS which support S-ATA HDD



Make any drive an External Drive! Keep your information protected on

these high quality Enclosures!



Accessories

Click part number to purchase online

CORPORATION

AE10289-ND

I

170426 / DA-70146

USB to serial adapter, USB 2.0

1

Accessories 117933 / DA-70118 AE10287-ND

USB 1.1 ⇒ PS/2 adapter

Click part number to purchase online **USB to Serial Converter, DSUB 9 pin** Male



Click part number to purchase online





Accessories 170426 / DA-70130 AE10290-ND USB repeater cable 2.0

Click part number to purchase online

DIGITUS® Pocket KVM switch PS/2, 2-port



- Controls two PCs with one PS/2 keyboard, one PS/2 mouse and one monitor
- Simple installation no additional software required
- · PC selection via hotkey
- Excellent video quality up to 1920 x 1440 pixels 200 MHz bandwidth Supports DDC, DDC2, DDC2B, DDC2AB
- Hot Plug & Play

- · Keyboard and mouse emulation for faultless booting of the computer
- Autoscan (5,10,15,20,25,30 sec. options) / autoskip function
- No external power supply required
- Integrated KVM cable for connection of two PCs 1.2 m
- Supports standard PS/2 mouse, Microsoft IntelliMouse and full support for Microsoft IntelliPoint 5.0 mouse driver and Loaitech Mouse Ware driver
- Supports Windows 95/98/98SE/ME/NT4.0/2000/XP/VISTA, DOS, Linux, Novell Netware, FreeBSD

DIGITUS® Pocket KVM switch PS/2, 2-port for USB PC



- · Control two PCs with one PS/2 keyboard, one PS/2 mouse and one monitor
- Simple installation no additional software required
- PC selection via hotkey
- Excellent video quality up to 1920 x 1440 pixels, 200 MHz bandwidth • Supports DDC, DDC2, DDC2B, DDC2AB
- Hot Plug & Play
- Keyboard and mouse emulation for faultless booting of the computer
- Autoscan (5,10,15,20,25,30 sec. options) / autoskip function
- No external power supply required
- Integrated KVM cable for connection of two PCs 1.5 m
- Supports standard PS/2 mouse, Microsoft IntelliMouse and full support for Microsoft IntelliPoint 5.0 mouse driver and Logitech Mouse Ware driver
- Supports Windows 95/98/98SE/ME/NT4.0/2000/XP, DOS, Linux, Novell Netware, FreeBSD

DIGITUS® USB-PS/2-KVM switch

• Mouse and keyboard connection to USB-port of the PC

DIGITUS® USB pocket KVM switch, 2-port



- · Control two PCs with one USB keyboard, one USB mouse and one monitor
- Simple installation: No additional software required
- PC selection via hotkey
- Excellent video quality-up to 2048 x 1536 pixels at 85 HZ
- Support DDC, DDC2, DDC2B, DDC2AB
- Audio IN/OUT support
- Hot Plug & Play
- Keyboard and mouse emulation for faultless booting of the computer
- Autoscan- (5 to 60 sec.)

206064 / DC-11402

USB pocket KVM switch, 2-port

- No external power supply required
- Integrated KVM cable for connection of two PCs 1.2 m Supports Windows 95/98/98SE/ME/NT4.0/2000/2003 Server/XP/VISTA,
- Linux, Mac and Sun Micro Systems

	Datacom		Datacom
159056 / DC-OC12 Pocket KVM switch PS/2, 2-port	DC-OC12-ND	159056 / DC-OC12U Pocket KVM switch PS/2, 2-port	DC-OC12U-ND
Click part number to purchase online		Click part number to purchase online	

Click part number to purchase online

DIGITUS® USB-KVM switch, 2-port



- · Controls two PCs with one PS/2 or USB-keyboard, one PS/2 or USB-mouse and one monitor
- Simple installation no additional software needed
- · PC-choice over push-buttons, Hot-Key or OSD-Utility
- Excellent video quality up to 1920 x 1440 pixels
- Supports DDC, DDC2
- Hot Plug & Play
- Emulates a keyboard on each PC to allow your computers to boot normally without a keyboard error
- Autoscan- (5 bis 250 sec.)
- USB Bus Powered and downstream-port activated by external Power DC 5V 2A
- incl. 3-Port USB Hub
- Supports Windows 95/98/98SE/ME/NT4.0/2000/2003 Server/XP/VISTA, Linux, Mac and Sun Micro Systems

- T E.F. 3 , lan iller and DIGITUS ۲ (1 H
- · Controls up to two PCs with one PS/2- or USB-keyboard, one PS/2or USB-mouse and one monitor
- Simple installation no additional software needed
- PC-choice over push-buttons or Hot-Key
- Excellent video quality up to 2048 x 1536 pixels at 85 Hz
- Supports DDC, DDC2
- Hot Plug & Play
- Emulates a keyboard on each PC to allow your computers to boot normally without a keyboard error
- Autoscan (5 to 250 sec.)

200994 / DC-11202-1

- No external power supply needed, self powered through PS/2 and/or USB connection
- (optional Power supply 5V; 2,0A Art.-Nr. DN-R-PS)
- Fully compliant with the USB 1.1/ 2.0 specification
- Supports Windows 95/98/98SE/ME/NT4.0/2000/2003 Server/XP/VISTA, Linux, Mac and Sun Micro Systems

DIGITUS® USB-PS/2-KVM switch

Click part number to purchase online

Datacom

DC-11402-ND



- Controls up to four PCs with one PS/2- or USB-keyboard, one PS/2or USB-mouse and one monitor
- Simple installation no additional software needed
- · PC-choice over push-buttons or Hot-Key
- Excellent video quality up to 2048 x 1536 pixels at 85 Hz
- Supports DDC, DDC2
- Hot Plug & Play
- Emulates a keyboard on each PC to allow your computers to boot normally without a keyboard error
- Autoscan (5 to 250 sec.)

201007 / DC-12202-1

IISB-PS/2-KVM switch, 4-port

- No external power supply needed, self powered through PS/2 and/or USB connection
- (optional Power supply 5V; 2,0A Art.-Nr. DN-R-PS)
- Fully compliant with the USB 1.1/2.0 specification • Supports Windows 95/98/98SE/ME/NT4.0/2000/2003 Server/XP/VISTA, Linux, Mac and Sun Micro Systems

Datacom 201076 / DC-11201-1 DC-11201-1-ND IISB-KVM switch, 2-port

Click part number to purchase online

USB-PS/2-KVM switch, 2-port Click part number to purchase online

Datacom

DC-11202-1-ND

Click part number to purchase online

Datacom

DC-12202-1-ND

DIGITUS® Wireless LAN USB 2.0 adapter, 802.11g

DIGITUS® Wireless LAN PCI adapter, 802,11g

- IEEE 802.11b and IEEE 802.11g compatible
- Compliant to USB 2.0 standard
- Supported data transfer rates 54,11,5.5,2.0,1.0 Mbps
- 128-bit WEP (Wired equivalent privacy) encryption
- WPA and WPA2 encryption (Wireless fidelity protected access)
- Realtek-Chipset
- Suitable for all current network environments
- Support for Windows 98SE/ME/2000/XP





- IEEE 802.11b and IEEE 802.11g compatible
- 32 bit PC card compatible
- Supported data transfer rates 54,11,5.5,2.0,1.0 Mbps
- 128-bit WEP (Wired equivalent privacy) encryption
- Support for WPA and WPA2
- Realtek-Chipset
- Suitable for all current network environments
- Support for Windows 98SE/ME/2000/XP/Vista



211655 / DN-7006GS **DN-7006GS-ND** Wireless LAN PCI adapter, 802,11a Click part number to purchase online @



- LC Display shows: Number of Access Points, Wi-Fi standard, Channel, SSID, encryption and Signal strength
- Shows several Access Points in the Wireless LAN environment
- Blue lightend, easy to read LC Display
- Integrated rechargeable long life battery, charged over the USB Port
- Easy to use, Simple function keys on the device
- Integrated USB Wireless LAN Adapter based on Zydas chipset
- IEEE 802.11b and IEEE 802.11g compatible
- Supported data transfer rate 54,11,5.5,2.0,1.0 Mbps
- Security: 64/128/256-bit WEP Data Encryption,
- WPA/WPA2 (TKIP with IEEE 802.1x) and AES
- · Suitable for all current network environments • Support for Windows XP,2000





195535 / DN-7020 **DN-7020-**N Wi-Fi Finder with integrated USB 2.0 wireless LAN adapter Click part number to purchase online @



Enjoy connections. Live.





- IEEE 802.3 and IEEE 802.3u compatible
- 20/200 MBit full duplex
- Automatic speed and half/full duplex detection / configuration
- Store and forward architecture
- Auto MDI / MDI-X function
- CE compliant
- External power supply

136750 / DN-5002C

N-Way Desktop Switch, 8-port





Click part number to purchase online

DN-5002C-ND



DIGITUS[®] Microscope camera with built-in light

The universal digital microscope camera shows objects in "live view" with up to 200x magnification on the computer screen. The built-in bright LED lighting guarantees for sharp and brilliant pictures.

 Universal microscope camera for the computer with built-in white and bright lighting

- Magnification continuous 10 200x
- Screen capture resolution 640 x 480 pixel
- "Live view" with up to 30 fps
- USB 1.1 / 2.0 interface
- 1,8m USB Cable length
- Ideal for business and hobby e.g.
- for industrial inspection like textile and printing,
- for skin and scalp examination,
- for stamp, coin and gem collectors,
- for science and learning.
- As reading aid.
- Incl. desktop stand, manual and capture software on CD-ROM
- For Windows-PC operating WIN98SE, ME, 2000, XP, Vista and Mac





	Multimedia	
200154 / DA-70350 Digital USB Microscope	<u>DA-70350-ND</u>	(DIGI-Key)
Click part numb	er to purchase online @	

Amazing 200x magnification and Live View at 30fps!

Perfect gift for everyone, even youself! Bright image and outstanding quality, built in 4 in 1 Card Reader!



DIGITUS® Digital photo frame

- 7" Screen size
- Memory card slot for SD and MMC memory cards
- Slideshow for JPEG files
- Slideshow interval adjustable
- Autoplay when inserting memory card
- Keys for the simple controlling of important functions (Play/Pause, Prev, Next, Interval, Modus)
- Vertically, horizontal arrangeable and additionally with hanging for wall fastening

Technical features

- Size: 7 inch
- Resolution: 480 x 234
- Brightness: 350 cd/m2
- Contrast: 300
- View angle: 60/60/5 (CR>10)
 Response time: 30 ms
- Response mile
 Format: JEPG

Digital photo frame

211358 / DA-70871

nedia DA-70871-ND Darshine (Constant)

Click part number to purchase online @

Multimedia

Top of the line USB HUBS & Card Readers!

DIGITUS[®] "Twister" notebook USB 2.0 Hub

- 4 x USB A female, each twistable about 180 degree
- 1 x USB A male, integrated and twistable about 180 degree
- Space-saving design, direct Pluggable to the notebook without additional cable
- High-quality "softtouch" material
- With status LED and connector for an additional power supply
- USB 2.0 and USB 1.1 compatible • Supports Hot Plug and Plug & Play
 - supports not Plug and Plug & Play





	Accessories
205890 / DA-70213-1 "Twister" notebook USB 2.0 Hub	<u>DA-70213-1-ND</u>
"	nber to purchase online @



Card reader USB 2.0 56in1 + Hub

Click part number to purchase online @



Built-in Microphone, Start your webconference right away!

211648 / DA-70814 USB webcam

Multimedia DA-70814-ND

DIGITUS® USB Bluetooth 2.0 EDR adapter

- Bluetooth 1.1 / 1.2 / 2.0 and USB 1.1 compatible
- Supported data rates: up to 3 Mbps(Max)
- Range: up to 80 m DN-3017, up to 150m DN-3018
- CSR Bluetooth Chipset
- Toshiba Bluetooth Software
- Suitable for Windows 98 SE / ME / 2000 / XP
- Dimension: (LxWxH) 59 x 7 x 19 mm
- Weight: 8 g

Bluetooth2.0 high speed



Turn your PC into a Bluettoth device the next edge on communications!



• Bluetooth Audio Transmitter: Plug into your Stereo audio source via audio jack in your

FE

100

Click part number to purchase online @

DIGITUS® Bluetooth audio transmitter

- MP3 .PSP, PC, TV, DVD player, ipod, home audio system ...etc.
- Compatible with Bluetooth 1.1 / 1.2 standard
- Data transfer rate up to 732 kbps
- Range up to approx. 15m
- Ultra-compact design
- Rechargeable polymer battery
- Working time up to 6,5 hours
- Automatically pair with Stereo
- Bluetooth headphone by pressing a button
- Support A2DP profile
- Size: 52 x 14 x 22 mm





Multimedia DN-3014-ND



U

DIGITUS® USB 2.0 IDE & SATA cable



Accessories <u>DA-70700-ND</u>

USB fingerprint-sensor - USB stick version Click part number to purchase online @

206019 / DA-70700

DIGITUS

Notebook cooler pad, with Hub and CardReader

205753 / DA-70341

is a Trademark of ASSMANN Electronics

DA-70341-ND

Accessories

Click part number to purchase online @