

## Specification Sheet

Part Number: TSRFW-JBD2



Rubber based foam tape adhesive with high ultimate bond strength conforms to any surface.

Dual Gang Junction Box, 2.77" Deep, 2-Piece, PVC, Office White, 1/bg

Article Number 250-20001

Type TSR-JBD2

Color Office White (OEWH)

Quantity Per bag

Product Description Offered in dual or single gang format, HellermannTyton's Low Voltage Junction Boxes are versatile enough for any network cabling application. Available in varying depths, these boxes are all equipped with concentric knockouts on all four sides for every TSR size of raceway to eliminate routing and installation inconvenience. all junction boxes come with adhesive strips on the back of the base and #6 screws to secure the box to the base.

Short Description Dual Gang Junction Box, 2.77" Deep, 2-Piece, PVC, Office White, 1/bg

|                  |                 |
|------------------|-----------------|
| Global Part Name | TSR-JBD2-PVC-WH |
|------------------|-----------------|

|                     |      |
|---------------------|------|
| Length L (Imperial) | 4.94 |
|---------------------|------|

|                   |        |
|-------------------|--------|
| Length L (Metric) | 125.48 |
|-------------------|--------|

|                    |      |
|--------------------|------|
| Width W (Imperial) | 5.02 |
|--------------------|------|

|                  |        |
|------------------|--------|
| Width W (Metric) | 127.51 |
|------------------|--------|

|                     |      |
|---------------------|------|
| Height H (Imperial) | 2.77 |
|---------------------|------|

|                   |       |
|-------------------|-------|
| Height H (Metric) | 70.36 |
|-------------------|-------|

|          |                         |
|----------|-------------------------|
| Material | Polyvinylchloride (PVC) |
|----------|-------------------------|

|                   |     |
|-------------------|-----|
| Material Shortcut | PVC |
|-------------------|-----|

|              |           |
|--------------|-----------|
| Flammability | UL 94 V-0 |
|--------------|-----------|

|              |    |
|--------------|----|
| Halogen Free | No |
|--------------|----|

|                       |    |
|-----------------------|----|
| UV Resistant (Yes/No) | No |
|-----------------------|----|

|                       |                |
|-----------------------|----------------|
| Operating Temperature | +122°F (+50°C) |
|-----------------------|----------------|

|                              |    |
|------------------------------|----|
| Reach Compliant (Article 33) | No |
|------------------------------|----|

|                |     |
|----------------|-----|
| ROHS Compliant | Yes |
|----------------|-----|

|                             |            |
|-----------------------------|------------|
| Package Quantity (Imperial) | 1          |
| Package Quantity (Metric)   | 1          |
| Customs Number              | 3925900000 |

### About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).