HellermannTyton

Specification Sheet

Part Number: 181-00641

Narrow fingers reduce fanning of wires to terminal blocks, providing a neater appearance.

Each finger features a double restriction to hold wires in the bottom portion of the duct, simplifying installation.

Mounting holes are uniform in size to those in slotted and solid wall duct but are provided every two inches to accommodate compact designs and provide ease of installation.

Nonpermanent adhesive allows repositioning prior to final installation.

High Density Slotted Wall Wiring Duct, 2" x 1", Adhesive, PVC, Gray, 120ft/Carton

Article Number	181-00641
Туре	SLHDA2X1
Color	Gray (GY)
Quantity Per	carton
Product Description	HellermannTyton High-Density Slotted Wall Wiring Duct features narrow fingers equaling a 2-to-1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.



Short Description	High Density Slotted Wall Wiring Duct, 2" x 1", Adhesive, PVC, Gray, 120ft/Carton	
Global Part Name	SLHDA2X1-PVC-GY	
Length L (Imperial)	6.0	
Length L (Metric)	1.83	
Fixation Method	Adhesive	
Width W (Imperial)	2.0	
Width W (Metric)	50.8	
Height H (Imperial)	1.06	
Height H (Metric)	26.9	
Mounting Hole Centers (Imperial)	2.0	
Material	Polyvinylchloride (PVC)	
Material Shortcut	PVC	
Halogen Free	No	
UV Resistant (Yes/No)	Νο	

Operating Temperature	+122°F (+50°C)	
Reach Compliant (Article 33)	No	
ROHS Compliant	Yes	
Certification/Specification	CSA EN 50085-1:2005 + A1:2013 EN 50085-2-3_1A UL	
UL Recognized (US)	Yes	
Package Quantity (Imperial)	120.0	
Package Quantity (Metric)	36.58	
Customs Number	3925900000	

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

Contact Us	RoHS/WEEE Compliance	Disclaimer	Terms and Conditions
------------	----------------------	------------	----------------------