

Specification Sheet

Part Number: 183-13737

Excellent fire-safety characteristics.

Narrow slots suitable for small-diameter wires.

Fingers can be removed with no sharp edges at pre-notched snap-off points.

Duct covers hold securely even in a vertical position and under vibration.



Halogen Free Slotted Wiring Duct, w/o Adhesive, 37.5mm x 37.5mm, PC/ABS, Gray RAL, 40 m/Box

Article Number 183-13737

Type HTWD-HF-37.5X37.5

Color Gray RAL 7035 (7035)

Quantity Per box

Product Description HellermannTyton HTWD-HF halogen-free ducts are used wherever

there are high demands on personal or material safety, such as public transport, tunnels, escalators and data processing centers. Snap-on covers are included with corresponding duct sizes to ensure complete wire protection. Base perforation according to DIN EN 50085. Note:

Halogen-free PC+ABS is not resistant to all oils and greases.

Short Description Halogen Free Slotted Wiring Duct, w/o Adhesive, 37.5mm x 37.5mm,

PC/ABS, Gray RAL, 40 m/Box

Global Part Name

HTWD-HF-37.5X37.5-PC/ABS-GY

Length L (Imperial)

6.56

Length L (Metric)

2

Fixation Method

Screw Mounting

Width W (Imperial)

1.48

Width W (Metric)

37.5

Height H (Imperial)

1.48

Height H (Metric)

37.5

Material

Acrylonitrile Butadiene Styrene alloyed with Polycarbonate (PC/ABS)

Material Shortcut

PC/ABS

Flammability

UL 94 V-0

Halogen Free

Yes

UV Resistant (Yes/No)

No

Operating Temperature

-13°F to +194°F (-25°C to +90°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant	Yes
Certification/Specification	UL ANSI/UL 62275 EN [45545-2]
UL Recognized (US)	Yes
Package Quantity (Imperial)	131.23
Package Quantity (Metric)	40
Customs Number	3925900000

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions