

ELECTRO-TAP

TE Internal #: 177766-1

Splices, Tap Splice, 24 – 22 AWG Wire Size, .2 – .4 mm² Wire Size, 404 – 643 CMA Wire Size, Brass, Length .472 in [12 mm], Bag, ELECTRO-TAP

[View on TE.com >](#)



Terminals & Splices > Splices



Splice Type: **Tap Splice**
Wire Size: **.2 – .4 mm²**
Sealable: **No**
Compatible Insulation Diameter Range: **4 mm [.157 in]**

Features

Product Type Features

Splice Accessory Type	Tap Cover
Splice Type	Tap Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Insulation Support

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Body Features

Product Weight	.877 g
----------------	--------

Contact Features

Terminal Plating Material	Tin
Contact Base Material	Brass

Housing Features

Housing Material	Nylon - GF
------------------	------------



Dimensions

Tap Wire Size	.18 – .36 mm²
Wire Size	404 – 643 CMA
Compatible Insulation Diameter Range	4 mm[.157 in]
Product Length	12 mm[.472 in]

Usage Conditions

Insulation Option	Fully Insulated
Operating Temperature Range	105 °C[221 °F]

Operation/Application

Compatible With Wire Base Material	Copper
------------------------------------	--------

Industry Standards

Government Qualified Splice	No
-----------------------------	----

Packaging Features

Packaging Quantity	500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) SVHC > Threshold: Melamine (3% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Do not handle until all safety precautions have been read and understood. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 177766-2
ELECTRO TAP ASSY, 24 - 22

Also in the Series | ELECTRO-TAP

Splices(13)

Customers Also Bought

TE Part #4-640440-2
12P MTA100 CONN ASSY 22AWG RED

TE Part #1379658-2
4W RCPT HSG CODING 2 GRAY

TE Part #1-643075-2
12P MTA100 MOLDED COVER

TE Part #1-1609112-4
15CBE1=F8274





TE Part #2205061-1
CA MICRO-MATCH MOW-MOW
6POS



TE Part #5227726-1
ISOLATED BNC SOLDER JACK ASSY



TE Part #917308-1
MINI MLC CONN REC CONT.



TE Part #1-2291193-3
SMARTSEAL TERMINAL



TE Part #166632-1
IEC-F F.CONT.COSI

Documents

Product Drawings

ELECTRO TAP ASSY

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_177766-1_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_177766-1_B.3d_igs.zip

English

Customer View Model

ENG_CVM_177766-1_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ELECTRO-TAP CABLE CONNECTOR/SPLICE

English

Product Specifications

Product Specification

English

AMP ELECTRO-TAP* Splice (AWG#22-#24)

English

177766-1

Splices, Tap Splice, 24 – 22 AWG Wire Size, .2 – .4 mm² Wire Size, 404 – 643 CMA
Wire Size, Brass, Length .472 in [12 mm], Bag, ELECTRO-TAP

