

## **SOLISTRAND**

TE Internal #: 36946

Splices, Parallel Splice, 1/0 AWG Wire Size, 41 - 60 mm<sup>2</sup> Wire Size, Standard, .444 in [11.27 mm] Barrel Inside Diameter, 83700 - 119500

CMA Wire Size

View on TE.com >



Terminals & Splices > Splices











Splice Type: Parallel Splice

Wire Size: 41 - 60 mm<sup>2</sup>

Sealable: No

Splice Features: Standard

## **Features**

# **Product Type Features**

Splice Accessory Type	Splice
Splice Type	Parallel Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support

## **Configuration Features**

Compatible With Wire & Cable Type	Discrete Wire

## **Body Features**

Product Weight	15.245 g	
Splice Features	Standard	

### **Contact Features**

	100 μin
Terminal Plating Material	Tin
Contact Base Material	Copper



Barrel Type	Closed
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Outside Diameter	15.58 mm[.613 in]
Wire Size	83700 - 119500 CMA
Barrel Inside Diameter	11.27 mm[.444 in]
Terminal Material Thickness	1.85 mm[.073 in]
Product Length	18.64 mm[.734 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	170 °C[338 °F]
Operation/Application	
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	50

# **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Loose Piece



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

# Compatible Parts




TE Part # 1490414-3 HYP10 SOLIS HD 1/0AWG INDENTER



TE Part # 36946-2 SOLIS, PARA 1/0 60/40 SN-PB














# **Customers Also Bought**

















TE Part # 356022-2 SLEEVE, SAFETY

TE Part # A52106-000 CI-239-301

## **Documents**

Product Drawings
SPLICE, SOLIS PARA 1/0

English

## **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_36946\_S.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_36946\_S.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_36946\_S.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the  ${\bf Terms}$  and  ${\bf Conditions}$  of use.

Datasheets & Catalog Pages

SOLISTRAND - QRG

English

## **Agency Approvals**

**UL Report** 

English

**UL Report** 

English

Splices, Parallel Splice, 1/0 AWG Wire Size, 41 - 60 mm² Wire Size, Standard, .444 in [11.27 mm] Barrel Inside Diameter, 83700 - 119500 CMA Wire Size

