

**Coax Cable Stripper, 1/2 and 1/4 inch lengths for RG59, RG6, RG7, RG11**

**Configuration**

Tool Type	Coax Cable Stripper
Cable Type	RG59, RG6, RG7, RG11

**Mechanical Specifications**

<b>Size</b>	
Length	8.5 in [215.9 mm]
Width	4.76 in [121 mm]
Height	1.1 in [27.94 mm]
Weight	0.094 lbs [42.64 g]

**Compliance Certifications** (see [product page](#) for current document)

**Notes:**

- Values at 25 °C, sea level

Coax Cable Stripper, 1/2 and 1/4 inch lengths for RG59, RG6, RG7, RG11 from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [Coax Cable Stripper, 1/2 and 1/4 inch lengths for RG59, RG6, RG7, RG11 FMTL5210](#)

URL: <https://www.fairviewmicrowave.com/coax-cable-stripper-rg59-rg6-rg7-rg11-fmtl5210-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



**Features:**

- Designed for use with coax (Video), twisted pair (Data), telephone round and flat (voice) and other multi-conductor, AWG cables
- U-shaped slot with blade height adjustment
- Integrated cable cutter
- 1/2" and 1/4" stripping lengths

Fairview Microwave  
 301 Leora Ln., Suite 100  
 Lewisville, TX 75056  
 Tel: 1-800-715-4396 / (972) 649-6678  
 Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	A	INITIAL RELEASE	03/23/2023	HBAKKE	AGANWANI

  

**FEATURES:**

- USED IN NETWORKING OF COAX (VIDEO), TWISTED PAIR (DATA), TELEPHONE ROUND AND FLAT (VOICE) AND OTHER MULTI-CONDUCTOR CABLES.
- FEATURES A U-SHAPED SLOT WITH BLADE HEIGHT ADJUSTMENT COMPATIBLE FOR CABLE OD FROM 3.2mm TO 9mm.
- INTEGRATED WITH A CABLE CUTTER FOR BETTER AND HANDY SOLUTION.
- FLAT CABLE 1/2" AND 1/4" STRIPPING LENGTH STOPS FOR FAST AND EFFICIENT WORK.
- BLACK VELCRO STRIP BRUSHES THE BRAIDS BACK OVER THE CABLE JACKET FOR EASY CONNECTOR TERMINATION.
- REVERSIBLE & INTERCHANGEABLE CASSETTES FOR A VARIETY OF CABLE APPLICATIONS.

  

<p><b>Fairview Microwave<sup>®</sup></b> an INFINIT<sup>®</sup> brand</p> <p>Website: <a href="http://www.FairviewMicrowave.com">www.FairviewMicrowave.com</a> Phone: 1.800.715.4396   1.972.649.6678</p>	<p>UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [ ] ARE MILLIMETERS</p> <p>TOLERANCES:  .X = ± .2 [ .5 ]     FRACTIONS ± .132  .XX = ± .02 [ .5 ]     ANGLES ± 1°  .XXX = ± .005 [ .13 ]</p> <p>CABLE LENGTH TOLERANCES:  512 (205) = +1 (25) / -0  &gt;12 (305) ≤ 60 (1524) = +2 (51) / -0  &gt;60 (1524) ≤ 120 (3048) = +4 (102) / -0  &gt;120 (3048) ≤ 300 (7620) = +6 (152) / -0  &gt;300 (7620) = +5% / -0</p>	<p>INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5 SHEET</p> <p>SCALE: NONE</p> <p>1 OF 1</p>
<p>DESCRIPTION: Tool, RG59/67/11, UTP/STP 2-Blade, Adjustable</p>		
SIZE: A	CAGE CODE: 3FKR5	ITEM NO.:
REV: A	DRAWN BY: HBAKKE	REV: A